



DL50-N2225

Dx50

TIME-OF-FLIGHT SENSORS

SICK
Sensor Intelligence.



Ordering information

| Type | part no. |
|------------|----------|
| DL50-N2225 | 1048419 |

Other models and accessories → www.sick.com/Dx50

Detailed technical data

Features

| | |
|---------------------------------------|--|
| Measuring range | 200 mm ... 50,000 mm, on “diamond grade” reflective tape |
| Target | Reflector |
| Resolution | 100 µm |
| Repeatability | ≥ 0.25 mm ^{1) 2) 3)} |
| Measurement accuracy | ± 3 mm ⁴⁾ |
| Response time | 10 ms ... 160 ms, 10 ms / 40 ms / 160 ms ^{2) 5)} |
| Output time | 2.5 ms ^{6) 7)} |
| Emitted beam | |
| Light source | Laser, red |
| Type of light | Visible red light |
| Typ. light spot size (distance) | 15 mm x 15 mm (10 m) |
| Key laser figures | |
| Normative reference | IEC 60825-1:2014, EN 60825-1:2014 |
| Laser class | 1 ⁸⁾ |
| Average laser service life (at 25 °C) | 100,000 h |
| Additional function | Set moving average fast/medium/slow Switching mode: distance to object (DtO) Teach-in, scaling and inversion of digital output Set hysteresis Multifunctional input and output: Laser off, external teach, digital output 2, deactivated Adjustable resolution of the SSI distance output: 0.0625 mm / 0.1 mm / 0.125 mm / 1 mm |

- 1) Equivalent to 1 σ.
- 2) Dependent on the averaging setting: fast/medium/slow.
- 3) Typical value.
- 4) 200 mm ... 4,000 mm: ≤ ± 5 mm.
- 5) Lateral entry of the object into the measuring range.
- 6) For baud rate 115,200 bps.
- 7) Continuous change of distance in measuring range.
- 8) Do not intentionally look into the laser beam. Never point the laser beam at people's eyes.
- 9) Wavelength: 658 nm; max. output: 80 mW; pulse duration: 2.5 ns; duty cycle: 1/240.

| | |
|----------------------------------|---|
| | Unique measurement value Crosstalk safety Switch-off display Reset to factory default Lock user interface |
| Safety-related parameters | |
| MTTF _D | 101 years |
| DC _{avg} | 0% |

- 1) Equivalent to 1 σ .
- 2) Dependent on the averaging setting: fast/medium/slow.
- 3) Typical value.
- 4) 200 mm ... 4,000 mm: $\leq \pm 5$ mm.
- 5) Lateral entry of the object into the measuring range.
- 6) For baud rate 115,200 bps.
- 7) Continuous change of distance in measuring range.
- 8) Do not intentionally look into the laser beam. Never point the laser beam at people's eyes.
- 9) Wavelength: 658 nm; max. output: 80 mW; pulse duration: 2.5 ns; duty cycle: 1/240.

Interfaces

| | |
|---------------------------------------|--|
| Serial | ✓, RS-422 |
| Digital output | |
| Number | 1 ... 2 ^{1) 2)} |
| Type | NPN |
| Function | Dependent on the set function MF: digital output 2 / laser off, external teach |
| Maximum output current I _A | ≤ 100 mA |
| Multifunctional input (MF) | - / 1 x ^{3) 4) 5)} |
| Hysteresis | 1 mm ... 1,000 mm |

- 1) Output Q short-circuit protected.
- 2) NPN: HIGH = < 2.5 V / LOW = V_S.
- 3) Dependent on the set function MF: digital output 2 / laser off, external teach.
- 4) Response time ≤ 60 ms.
- 5) NPN: HIGH = ≤ 2.5 V / LOW = V_S.

Electronics

| | |
|-------------------------------------|--|
| Supply voltage U_B | DC 10 V ... 30 V ¹⁾ |
| Power consumption | ≤ 2.1 W ²⁾ |
| Ripple | ≤ 5 V _{pp} ³⁾ |
| Initialization time | ≤ 250 ms |
| Warm-up time | ≤ 15 min |
| Display | LC display, 2 x LED |
| Enclosure rating | IP65 |
| Protection class | III |
| Connection type | Male connector, M12, 8-pin |

- 1) Limit values, reverse-polarity protected, operation in short-circuit protected network: max. 8 A.
- 2) Without load.
- 3) May not fall short of or exceed V_S tolerances.

Mechanics

| | |
|-------------------------------|-----------------------------|
| Dimensions (W x H x D) | 36.1 mm x 62.7 mm x 57.7 mm |
| Housing material | Metal (zinc diecast) |
| Window material | Plastic (PMMA) |
| Weight | 200 g |

Ambient data

| | |
|--|--|
| Ambient temperature, operation | -30 °C ... +65 °C -30 °C ... +80 °C, operation with 2 cooling plates -30 °C ... +140 °C, operation with 2 cooling plates and protection filter |
| Ambient temperature, storage | -40 °C ... +75 °C |
| Max. rel. humidity (not condensing) | ≤ 95 % |
| Typ. Ambient light immunity | 40,000 lx |
| Vibration resistance | EN 60068-2-6, EN 60068-2-64 |
| Shock resistance | EN 60068-2-27 |

Classifications

| | |
|-----------------------|----------|
| ECLASS 5.0 | 27270801 |
| ECLASS 5.1.4 | 27270801 |
| ECLASS 6.0 | 27270801 |
| ECLASS 6.2 | 27270801 |
| ECLASS 7.0 | 27270801 |
| ECLASS 8.0 | 27270801 |
| ECLASS 8.1 | 27270801 |
| ECLASS 9.0 | 27270801 |
| ECLASS 10.0 | 27270801 |
| ECLASS 11.0 | 27270801 |
| ECLASS 12.0 | 27270916 |
| ETIM 5.0 | EC001825 |
| ETIM 6.0 | EC001825 |
| ETIM 7.0 | EC001825 |
| ETIM 8.0 | EC001825 |
| UNSPSC 16.0901 | 41111613 |


Dimensional drawing




Dimensions in mm (inch)

- ① optical axis, sender
- ② optical axis, receiver
- ③ fixing hole
- ④ Reference surface = 0 mm
- ⑤ Status indicator digital output Q₁ (orange)
- ⑥ DT50 / DT50 Hi/DL50: Status display for supply voltage active (green), DS50 / DL50 Hi: Status display of digital output Q₂ (orange)
- ⑦ Control elements and display

Connection type Male connector M12, 8-pin




Connection diagram



- ① Multifunctional in- and output

Recommended accessories

Other models and accessories → www.sick.com/Dx50

| | Brief description | Type | part no. |
|---|---|---------------------------------|----------|
| device protection and care | | | |
|  | <ul style="list-style-type: none"> Description: Weather protection hood for Dx35 / Dx50 / Dx50-2 / Dx80 | OBW-KHS-M02 | 2050205 |
|  | <ul style="list-style-type: none"> Description: Cooling plate for Dx50/Dx50-2/DT20 (for water cooling) Usable for: DT20 Hi, Dx50, Dx50-2 | BEF-KP-Dx50/DT20 | 2055755 |
|  | <ul style="list-style-type: none"> Description: Thermal shield for Dx50 with NIR filter, for use with 2x cold plate BEF-KP-Dx50/DT20 | Heat protection filter for Dx50 | 2057137 |
| Mounting systems | | | |
|  | <ul style="list-style-type: none"> Description: Alignment unit Material: Steel Details: Steel, zinc coated Items supplied: Mounting hardware for the sensor included | BEF-AH-DX50 | 2048397 |
| reflectors and optics | | | |
|  | <ul style="list-style-type: none"> Description: Reflector plate, "diamond grade" reflective tape, 330 mm x 330 mm, base plate material: aluminum, screw connection Ambient operating temperature: -34 °C ... +70 °C | PL240DG | 1017910 |
| connectors and cables | | | |
|  | <ul style="list-style-type: none"> Description: Shielded Connection type head A: Female connector, M12, 8-pin, straight Connection type head B: Flying leads Cable: 2 m, 8-wire, PUR, halogen-free Connection systems: Flying leads Application: Zones with oils and lubricants | YF2A68-020XXXXLEAX | 6032448 |

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com