

TIC102 Slave

TICx02

PROFILING SYSTEMS





Ordering information

Туре	part no.
TIC102 Slave	1055104

Included in delivery: LMS111-10100S05 (2)

Other models and accessories → www.sick.com/TICx02



Detailed technical data

Features

-
Traffic management Toll collection
TIC102 Slave (For system extension)
LMS511 SE (2 x)
1
Up to 4 lanes
Yes, by means of additional LMS511 SE
2-scanner solution
Vehicle classes Driving direction Speed monitoring Lane assignment Confidence level for all vehicle datas Point cloud
Up to 30 classes
> 1.5 m,
Yes
Yes 1, eye-safe (IEC 60825-1:2014)
1, eye-safe (IEC 60825-1:2014)

Mechanics/electronics

Supply voltage	24 V DC (22.8 V DC 25.2 V DC)
Power consumption	120 W, With heating 41 W, without heating
Housing dimensions (W x D x H)	498 mm x 411 mm x 191 mm (Only mounting plate with pre-installed LMS511 SE)
Weight	15 kg
Installation position	Overhead
Installation height	6 m: 5 m 8 m
Enclosure rating	IP66 (EN 60529)

Performance

Counting accuracy	> 99.85 %
Classification accuracy	Typ. 98 % (For TLS8+1 classes)

Interfaces

Ethernet	√ (2)
Function	Sensor interface
Electrical connection	2 x connector ETH_Internal (M12) for sensor interface

Ambient data

Ambient operating temperature	-40 °C +60 °C
Ambient temperature, storage	-40 °C +70 °C

General notes

Items supplied	System housing including 2x 2D LiDAR sensors
----------------	----------------------------------------------

Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
China RoHS	✓

Classifications

ECLASS 5.0	27281001
ECLASS 5.1.4	27280190
ECLASS 6.0	27280190
ECLASS 6.2	27280190
ECLASS 7.0	27280190
ECLASS 8.0	27280190
ECLASS 8.1	27280190
ECLASS 9.0	27280190
ECLASS 10.0	27280190
ECLASS 11.0	27280190
ECLASS 12.0	27280190
UNSPSC 16.0901	41111615

Recommended accessories

Other models and accessories → www.sick.com/TICx02

	Brief description	Туре	part no.
connectors ar	nd cables		
	 Connection type head A: Female connector, 7/8", 5-pin, straight Connection type head B: Flying leads Cable: 30 m, 5-wire Description: Shielded 	Connecting ca- ble (female con- nector - open)	6045327

	Brief description	Туре	part no.	
	Connection systems: Flying leads			
1000	 Connection type head A: Male connector, M12, 4-pin, straight, D-coded Connection type head B: Male connector, M12, 4-pin, straight, D-coded Signal type: PROFINET Cable: 15 m, AWG22, PUR, halogen-free Description: PROFINET, shielded 	Connection ca- ble (male connec- tor-male connector)	6045328	
	 Connection type head A: Male connector, M12, 4-pin, straight, D-coded Connection type head B: Male connector, RJ45, 4-pin, straight Signal type: Ethernet, PROFINET Cable: 30 m, 4-wire, AWG26, PUR, halogen-free Description: Ethernet, shielded, PROFINET 	YM2D24-300EA1M- RJA4	6045311	
Mounting syst	Mounting systems			
	Description: Mounting bracket	Mounting bracket	4068061	
device protection and care				
	Description: Weather hood for TIC102	Weather pro- tection hood	4068062	

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

