Data sheet

MPS-192TLTQ0

MPS-T

CYLINDER SENSORS

SICK
Sensor Intelligence.

Ordering information

Type	part no.
MPS-192TLTQ0	1062519

Other models and accessories ➜ www.sick.com/MPS-T

Detailed technical data

Features

Cylinder type	T-slot
Cylinder types with adapter	Round body cylinder Profile cylinders and tie-rod cylinders Dovetail groove cylinder
Measuring range	192 mm [1]
Housing length	205 mm
Output function	IO-Link
Electrical wiring	DC 4-wire
Enclosure rating	IP67 [2]
Adjustment	
Teach-in control panel	Resetting the measuring range to factory settings
IO-Link	Key lock Teaching in the measuring range Resetting the measuring range
IO-Link functions	Standard functions

[1] ± 1 mm.
[2] According to EN 60529.

Mechanics/electronics

Supply voltage	15 V DC ... 30 V DC

[1] FSR: Full Scale Range; max. measuring range.
[2] At 25 ° C, linearity error (maximum deviation) depending on response curve and minimal deviation function.
[3] At 25 ° C, repeatability magnet movement in one direction.
[4] Only in standard mode, not in IO-Link mode.
[5] The analog measured value can deviate for up to 100 ms under transient conditions.

Power consumption	25 mA, without load
Protection class	III
Time delay before availability	1.5 s
Required magnetic field sensitivity, typ.	4 mT ... 30 mT
Resolution, typ.	0.03 % FSR (max. ≥ 0.05 mm) [1]
Linearity error, typ.	0.3 mm [2]
Repeat accuracy, typ.	0.06 % FSR (≥ 0.1 mm) [3]
Sampling rate, typ.	1 ms [4]
Reverse polarity protection	Yes
Short-circuit protection	Yes
Status indicator LED	Yes
Teach-in	Yes
Ambient operating temperature	–20 °C ... +70 °C
Shock and vibration resistance	30 g, 11 ms / 10 ... 55 Hz, 1 mm
EMC	According to EN 60947-5-7 [5]
Connection type	Cable with M12 male connector, 4-pin, 0.3 m
Connection type Detail	
Deep-freeze property	Do not bend below 0 °C
Conductor cross section	0.08 mm²
Cable diameter	Ø 2.6 mm
Bending radius	With fixed installation > 5 x cable diameter
	For flexible use > 10 x cable diameter
Cable outlet	Axial
Material	
Housing	Plastic
Cable	PUR
UL File No.	NRKH.E181493 & NRKH7.E181493

[1] FSR: Full Scale Range; max. measuring range.
[2] At 25 ° C, linearity error (maximum deviation) depending on response curve and minimal deviation function.
[3] At 25 ° C, repeatability magnet movement in one direction.
[4] Only in standard mode, not in IO-Link mode.
[5] The analog measured value can deviate for up to 100 ms under transient conditions.

Safety-related parameters

$MTTF_D$	243 years
DC_{avg}	0 %
T_M (mission time)	20 years

Communication interface

Communication interface	IO-Link V1.1
Communication Interface detail	COM2
Cycle time	2.3 ms
Process data length	16 Bit

Process data structure	Bit 0 ... 15 = position (in 1 mm/128)

Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓
cULus certificate	✓
IO-Link certificate	✓
Information according to Art. 3 of Data Act (Regulation EU 2023/2854)	✓

Classifications

ECLASS 5.0	27270104
ECLASS 5.1.4	27270104
ECLASS 6.0	27270104
ECLASS 6.2	27270104
ECLASS 7.0	27270104
ECLASS 8.0	27270104
ECLASS 8.1	27270104
ECLASS 9.0	27270104
ECLASS 10.0	27270104
ECLASS 11.0	27270104
ECLASS 12.0	27274301
ETIM 5.0	EC002544
ETIM 6.0	EC002544
ETIM 7.0	EC002544
ETIM 8.0	EC002544
UNSPSC 16.0901	39122230

Installation note



Connection diagram Cd-179



Dimensional drawing Cable with connector M12, with knurled nut, Teach-in



	Total length (L1) mm	Measuring range (L2) mm	Distance mounting screws (L3) mm
MPS-32	45	32	40
MPS-64	77	64	72
MPS-96	109	96	104
MPS-128	141	128	136
MPS-160	173	160	168
MPS-192	205	192	200
MPS-224	237	224	232
MPS-256	269	256	264

Dimensions in mm (inch)
① function indicator
② Fixing screw SW 1.5
③ Teach-in button
④ Connection

Part no.	Type	L	Number of cores
1097751	MPS-032TSTQDS06	600 mm	4
1062506	MPS-032TLTQ0	300 mm	4
1062507	MPS-064TLTQ0	300 mm	4
1062508	MPS-096TLTQ0	300 mm	4
1062518	MPS-128TLTQ0	300 mm	4
1062521	MPS-160TLTQ0	300 mm	4
1062519	MPS-192TLTQ0	300 mm	4
1062522	MPS-224TLTQ0	300 mm	4
1062520	MPS-256TLTQ0	300 mm	4
1096343	MPS-128TSTQD	250 mm	3

Recommended accessories

Other models and accessories ➜ www.sick.com/MPS-T

	Brief description	Type	part no.
Mounting systems			
	• **Description:** Mounting bracket for mounting on SMC rails ECDQ2 (T-slot) • **Material:** Aluminum • **Details:** Aluminum • **Items supplied:** Without mounting hardware	BEF-KHZ-TT1	2046439
	• **Description:** Mounting bracket for mounting on SMC rails CDQ2 (T-slot) • **Material:** Aluminum • **Details:** Aluminum • **Items supplied:** Without mounting hardware	BEF-KHZ-TT2	2046440
	• **Description:** Mounting bracket for cylinder with dovetail slot • **Material:** Aluminum • **Details:** Aluminum • **Items supplied:** Without mounting hardware	BEF-KHZ-ST1	2022703
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 16 mm, ambient temperature min 0 °C max 50 °C • **Dimensions (W x H x L):** 26.6 m • **Material:** Plastic, Aluminum • **Details:** Plastic, Aluminum • **Packing unit:** 1 piece • **Suitable for:** T-slot	BEF-KHZ-RT-16	2077680
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 8 mm ... 130 mm, ambient temperature min –30 °C max 80 °C • **Material:** Stainless steel, Zinc cast • **Details:** Stainless steel, Zinc cast • **Packing unit:** 1 piece • **Suitable for:** T-slot	BEF-KHZ-RT1-130	2077684
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 12 mm, ambient temperature min 0 °C max 50 °C • **Dimensions (W x H x L):** 22.4 m • **Material:** Plastic, Aluminum • **Details:** Plastic, Aluminum • **Packing unit:** 1 piece • **Suitable for:** T-slot	BEF-KHZ-RT-12	2077681
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 8 mm ... 25 mm, ambient temperature min –30 °C max 80 °C • **Material:** Stainless steel, Zinc cast • **Details:** Stainless steel, Zinc cast • **Packing unit:** 1 piece • **Suitable for:** T-slot	BEF-KHZ-RT1-25	2077682
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 8 mm ... 63 mm, ambient temperature min –30 °C max 80 °C • **Material:** Stainless steel, Zinc cast • **Details:** Stainless steel, Zinc cast • **Packing unit:** 1 piece • **Suitable for:** T-slot	BEF-KHZ-RT1-63	2077683
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 20 mm, ambient temperature min 0 °C max 50 °C • **Dimensions (W x H x L):** 30.6 m • **Material:** Plastic, Aluminum • **Details:** Plastic, Aluminum • **Packing unit:** 1 piece • **Suitable for:** T-slot	BEF-KHZ-RT-20	2077679
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 25 mm, ambient temperature min 0 °C max 50 °C • **Dimensions (W x H x L):** 35.7 m • **Material:** Plastic, Aluminum • **Details:** Plastic, Aluminum • **Packing unit:** 1 piece	BEF-KHZ-RT-25	2077678

	Brief description	Type	part no.
	• **Suitable for:** T-slot		
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 32 mm, ambient temperature min 0 °C max 50 °C • **Dimensions (W x H x L):** 42.9 m • **Material:** Plastic, Aluminum • **Details:** Plastic, Aluminum • **Packing unit:** 1 piece • **Suitable for:** T-slot	BEF-KHZ-RT-32	2077677
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 40 mm, ambient temperature min 0 °C max 50 °C • **Dimensions (W x H x L):** 50.9 m • **Material:** Plastic, Aluminum • **Details:** Plastic, Aluminum • **Packing unit:** 1 piece • **Suitable for:** T-slot	BEF-KHZ-RT-40	2077676
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 50 mm, ambient temperature min 0 °C max 50 °C • **Dimensions (W x H x L):** 61.8 m • **Material:** Plastic, Aluminum • **Details:** Plastic, Aluminum • **Packing unit:** 1 piece • **Suitable for:** T-slot	BEF-KHZ-RT-50	2077675
	• **Description:** Mounting bracket on round body cylinder with piston diameter of 63 mm, ambient temperature min 0 °C max 50 °C • **Dimensions (W x H x L):** 73.9 m • **Material:** Plastic, Aluminum • **Details:** Plastic, Aluminum • **Packing unit:** 1 piece • **Suitable for:** T-slot	BEF-KHZ-RT-63	2077674
	• **Description:** Mounting bracket for integrated profile cylinder/tie-rod cylinder • **Material:** Zinc diecast • **Details:** Zinc diecast • **Items supplied:** Mounting hardware included	BEF-KHZ-PT1	2022702
	• **Description:** Label Holder, 2.5 mm to 3.5 mm, 10 pcs. • **Material:** Plastic • **Details:** TPU • **Packing unit:** 10 pieces	LABEL HOLDER	2086019
	• **Description:** Cable clips T-slot, 10 pcs./bag	CABLE CLIPS	2059322

	Brief description	Type	part no.
connectors and cables			
	• **Connection type head A:** Female connector, M12, 4-pin, straight, A-coded • **Description:** Unshielded • **Connection systems:** Screw-type terminals • **Permitted cross-section:** ≤ 0.75 mm²	DOS-1204-G	6007302
	• **Connection type head A:** Female connector, M12, 4-pin, angled, A-coded • **Description:** Unshielded • **Connection systems:** Screw-type terminals • **Permitted cross-section:** ≤ 0.75 mm²	DOS-1204-W	6007303
	• **Connection type head A:** Male connector, M12, 4-pin, straight, A-coded • **Description:** Unshielded • **Connection systems:** Screw-type terminals • **Permitted cross-section:** ≤ 0.75 mm²	STE-1204-G	6009932
	• **Connection type head A:** Male connector, M12, 4-pin, angled, A-coded • **Description:** Unshielded • **Connection systems:** Screw-type terminals • **Permitted cross-section:** ≤ 0.75 mm²	STE-1204-W	6022084
	• **Connection type head A:** Female connector, M12, 4-pin, straight, A-coded • **Connection type head B:** Flying leads • **Signal type:** Sensor/actuator cable • **Cable:** 2 m, 4-wire, PUR, halogen-free • **Description:** Sensor/actuator cable, unshielded • **Application:** Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YF2A14-020UB3XLEAX	2095607
	• **Connection type head A:** Female connector, M12, 4-pin, straight, A-coded • **Connection type head B:** Flying leads • **Signal type:** Sensor/actuator cable • **Cable:** 5 m, 4-wire, PUR, halogen-free • **Description:** Sensor/actuator cable, unshielded • **Application:** Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YF2A14-050UB3XLEAX	2095608
	• **Connection type head A:** Female connector, M12, 4-pin, angled, A-coded • **Connection type head B:** Flying leads • **Signal type:** Sensor/actuator cable • **Cable:** 2 m, 4-wire, PUR, halogen-free • **Description:** Sensor/actuator cable, unshielded • **Application:** Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YG2A14-020UB3XLEAX	2095766
	• **Connection type head A:** Female connector, M12, 4-pin, angled, A-coded • **Connection type head B:** Flying leads • **Signal type:** Sensor/actuator cable • **Cable:** 5 m, 4-wire, PUR, halogen-free • **Description:** Sensor/actuator cable, unshielded • **Application:** Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YG2A14-050UB3XLEAX	2095767
	• **Connection type head A:** Female connector, M12, 4-pin, straight, A-coded • **Connection type head B:** Flying leads • **Signal type:** Sensor/actuator cable • **Cable:** 0.6 m, 4-wire, PUR, halogen-free • **Description:** Sensor/actuator cable, unshielded • **Application:** Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YF2A14-C60UB3XLEAX	2145654
	• **Connection type head A:** Female connector, M12, 4-pin, straight, A-coded • **Connection type head B:** Flying leads • **Signal type:** Sensor/actuator cable • **Cable:** 1 m, 4-wire, PUR, halogen-free • **Description:** Sensor/actuator cable, unshielded • **Application:** Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YF2A14-010UB3XLEAX	2145655
	• **Connection type head A:** Female connector, M12, 4-pin, straight, A-coded • **Connection type head B:** Flying leads • **Signal type:** Sensor/actuator cable • **Cable:** 3 m, 4-wire, PUR, halogen-free • **Description:** Sensor/actuator cable, unshielded • **Application:** Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YF2A14-030UB3XLEAX	2145656
	• **Connection type head A:** Female connector, M12, 4-pin, angled, A-coded • **Connection type head B:** Flying leads • **Signal type:** Sensor/actuator cable • **Cable:** 0.6 m, 4-wire, PUR, halogen-free • **Description:** Sensor/actuator cable, unshielded	YG2A14-C60UB3XLEAX	2145657

	Brief description	Type	part no.
	• **Application:** Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation		
	• **Connection type head A:** Female connector, M12, 4-pin, angled, A-coded • **Connection type head B:** Flying leads • **Signal type:** Sensor/actuator cable • **Cable:** 1 m, 4-wire, PUR, halogen-free • **Description:** Sensor/actuator cable, unshielded • **Application:** Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YG2A14-010UB3XLEAX	2145658

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com

SICK
Sensor Intelligence.