



# GRTE18-P1162V

## GR18

PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.




Ordering information

| Type          | part no. |
|---------------|----------|
| GRTE18-P1162V | 1085705  |

Other models and accessories → [www.sick.com/GR18](http://www.sick.com/GR18)

Illustration may differ



Detailed technical data

Features

|                                 |                                 |
|---------------------------------|---------------------------------|
| Functional principle            | Photoelectric proximity sensor  |
| Functional principle detail     | Energetic                       |
| Dimensions (W x H x D)          | 18 mm x 18 mm x 73.5 mm         |
| Housing design (light emission) | Cylindrical                     |
| Housing length                  | 73.5 mm                         |
| Thread length                   | 49.3 mm                         |
| Thread diameter (housing)       | M18 x 1                         |
| Optical axis                    | Axial                           |
| Sensing range max.              | 5 mm ... 1,000 mm <sup>1)</sup> |
| Sensing range                   | 10 mm ... 800 mm <sup>1)</sup>  |
| Type of light                   | Visible red light               |
| Light source                    | LED <sup>2)</sup>               |
| Light spot size (distance)      | Ø 45 mm (800 mm)                |
| Wave length                     | 650 nm                          |
| Adjustment                      | Potentiometer, 270 °            |
| Display                         |                                 |
|                                 | LED green                       |
|                                 | Operating indicator             |
|                                 | Static on: power on             |
|                                 | LED yellow                      |
|                                 | Status of received light beam   |
|                                 | Static on: object present       |
|                                 | Static off: object not present  |

<sup>1)</sup> Object with 90% remission (based on standard white, DIN 5033).

<sup>2)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

|                             |                             |
|-----------------------------|-----------------------------|
| <b>Special applications</b> | Hygienic and washdown zones |
|-----------------------------|-----------------------------|

<sup>1)</sup> Object with 90% remission (based on standard white, DIN 5033).

<sup>2)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

## Mechanics/electronics

|                                            |                                                        |
|--------------------------------------------|--------------------------------------------------------|
| <b>Supply voltage U<sub>B</sub></b>        | 10 V DC ... 30 V DC <sup>1)</sup>                      |
| <b>Ripple</b>                              | < 5 V <sub>pp</sub> <sup>2)</sup>                      |
| <b>Current consumption</b>                 | 30 mA                                                  |
| <b>Switching output</b>                    | PNP                                                    |
| <b>Output function</b>                     | Complementary                                          |
| <b>Switching mode</b>                      | Light/dark switching <sup>3)</sup>                     |
| <b>Signal voltage PNP HIGH/LOW</b>         | V <sub>S</sub> - (≤ 3 V) / approx. 0 V                 |
| <b>Output current I<sub>max.</sub></b>     | ≤ 100 mA <sup>4)</sup>                                 |
| <b>Response time</b>                       | < 1,000 μs <sup>5)</sup>                               |
| <b>Switching frequency</b>                 | 500 Hz <sup>6)</sup>                                   |
| <b>Connection type</b>                     | Cable, 4-wire, 2 m <sup>7)</sup>                       |
| <b>Cable material</b>                      | Plastic, PVC                                           |
| <b>Conductor cross section</b>             | 0.14 mm <sup>2</sup>                                   |
| <b>Cable diameter</b>                      | Ø 4.8 mm                                               |
| <b>Circuit protection</b>                  | A <sup>8)</sup><br>B <sup>9)</sup><br>D <sup>10)</sup> |
| <b>Protection class</b>                    | III                                                    |
| <b>Weight</b>                              | 175 g                                                  |
| <b>Housing material</b>                    | Metal, Stainless steel V4A (1.4404, 316L)              |
| <b>Optics material</b>                     | Plastic, PMMA                                          |
| <b>Tightening torque, max.</b>             | 90 Nm                                                  |
| <b>Enclosure rating</b>                    | IP67<br>IP68 <sup>11)</sup><br>IP69K <sup>12)</sup>    |
| <b>Items supplied</b>                      | Fastening nuts (2 x)                                   |
| <b>Electromagnetic compatibility (EMC)</b> | EN 60947-5-2                                           |

<sup>1)</sup> Limit values. Operated in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not fall below or exceed U<sub>V</sub> tolerances.

<sup>3)</sup> Q = light switching;  $\bar{Q}$  = dark switching.

<sup>4)</sup> At U<sub>V</sub> > 24 V or ambient temperature > 49 °C, I<sub>A</sub> max. = 50 mA.

<sup>5)</sup> Signal transit time with resistive load.

<sup>6)</sup> With light/dark ratio 1:1.

<sup>7)</sup> Do not bend below 0 °C.

<sup>8)</sup> A = V<sub>S</sub> connections reverse-polarity protected.

<sup>9)</sup> B = inputs and output reverse-polarity protected.

<sup>10)</sup> D = outputs overcurrent and short-circuit protected.

<sup>11)</sup> According to EN 60529 (10 m water depth / 24 h).

<sup>12)</sup> According to ISO 20653:2013-03.

<sup>13)</sup> At U<sub>V</sub> ≤ 24V and I<sub>A</sub> < 50mA.

|                                      |                                  |
|--------------------------------------|----------------------------------|
| <b>Ambient operating temperature</b> | -25 °C ... +55 °C <sup>13)</sup> |
| <b>Ambient temperature, storage</b>  | -30 °C ... +75 °C                |
| <b>UL File No.</b>                   | E348498                          |

<sup>1)</sup> Limit values. Operated in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not fall below or exceed  $U_V$  tolerances.

<sup>3)</sup> Q = light switching;  $\bar{Q}$  = dark switching.

<sup>4)</sup> At  $U_V > 24$  V or ambient temperature  $> 49$  °C,  $I_A$  max. = 50 mA.

<sup>5)</sup> Signal transit time with resistive load.

<sup>6)</sup> With light/dark ratio 1:1.

<sup>7)</sup> Do not bend below 0 °C.

<sup>8)</sup> A =  $V_S$  connections reverse-polarity protected.

<sup>9)</sup> B = inputs and output reverse-polarity protected.

<sup>10)</sup> D = outputs overcurrent and short-circuit protected.

<sup>11)</sup> According to EN 60529 (10 m water depth / 24 h).

<sup>12)</sup> According to ISO 20653:2013-03.

<sup>13)</sup> At  $U_V \leq 24$  V and  $I_A < 50$  mA.

### Safety-related parameters

|                                     |             |
|-------------------------------------|-------------|
| <b>MTTF<sub>D</sub></b>             | 1,408 years |
| <b>DC<sub>avg</sub></b>             | 0%          |
| <b>T<sub>M</sub> (mission time)</b> | 20 years    |

### Certificates



|                                                          |   |
|----------------------------------------------------------|---|
| <b>EU declaration of conformity</b>                      | ✓ |
| <b>UK declaration of conformity</b>                      | ✓ |
| <b>ACMA declaration of conformity</b>                    | ✓ |
| <b>Moroccan declaration of conformity</b>                | ✓ |
| <b>China RoHS</b>                                        | ✓ |
| <b>ECOLAB certificate</b>                                | ✓ |
| <b>cULus certificate</b>                                 | ✓ |
| <b>Photobiological safety (DIN EN 62471) certificate</b> | ✓ |

### Classifications


|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27270903 |
| <b>ECLASS 5.1.4</b> | 27270903 |
| <b>ECLASS 6.0</b>   | 27270903 |
| <b>ECLASS 6.2</b>   | 27270903 |
| <b>ECLASS 7.0</b>   | 27270903 |
| <b>ECLASS 8.0</b>   | 27270903 |
| <b>ECLASS 8.1</b>   | 27270903 |
| <b>ECLASS 9.0</b>   | 27270903 |
| <b>ECLASS 10.0</b>  | 27270904 |
| <b>ECLASS 11.0</b>  | 27270904 |
| <b>ECLASS 12.0</b>  | 27270903 |
| <b>ETIM 5.0</b>     | EC001821 |
| <b>ETIM 6.0</b>     | EC001821 |

|                |          |
|----------------|----------|
| ETIM 7.0       | EC002719 |
| ETIM 8.0       | EC002719 |
| UNSPSC 16.0901 | 39121528 |


Adjustments GRTB18(S) Inox, GRTE18(S) Inox, Sensing range setting: Potentiometer, 270°



Connection diagram Cd-094




Characteristic curve GRTE18, 800 mm




- ① Sensing range on black, 6% remission factor
- ② sensing range to gray, 20% remission factor
- ③ Sensing range on white, 90% remission factor

Light spot size GRTE18, 800 mm




Sensing range diagram GRTE18, 800 mm




- ① Sensing range on black, 6% remission factor
- ② sensing range to gray, 20% remission factor
- ③ Sensing range on white, 90% remission factor

## Response range GRTE18, 800 mm



## Dimensional drawing GR18 Inox, cable, straight



Dimensions in mm (inch)

- ① Connection
- ② Threaded mounting hole M18 x 1
- ③ fastening nuts (2 x); width across 24, stainless steel
- ④ Potentiometer, 270°
- ⑤ LED indicator (4 x)
- ⑥ optical axis, receiver
- ⑦ optical axis, sender

Recommended accessories

Other models and accessories → [www.sick.com/GR18](http://www.sick.com/GR18)

|                                                                                   | Brief description                                                                                                                                                                                                                                                                                 | Type        | part no. |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|----------|
| Mounting systems                                                                  |                                                                                                                                                                                                                                                                                                   |             |          |
|  | <ul style="list-style-type: none"><li>• <b>Description:</b> Mounting bracket for M18 sensors</li><li>• <b>Material:</b> Stainless steel</li><li>• <b>Details:</b> Stainless steel</li><li>• <b>Items supplied:</b> Without mounting hardware</li></ul>                                            | BEF-WN-M18N | 5320947  |
| connectors and cables                                                             |                                                                                                                                                                                                                                                                                                   |             |          |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Male connector, M12, 4-pin, straight, A-coded</li><li>• <b>Description:</b> Unshielded</li><li>• <b>Connection systems:</b> Screw-type terminals</li><li>• <b>Permitted cross-section:</b> ≤ 0.75 mm<sup>2</sup></li></ul> | STE-1204-G  | 6009932  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)