



# DBS36E-S3AZ0S115

DBS36/50

INCREMENTAL ENCODERS

**SICK**  
Sensor Intelligence.



Illustration may differ



### Ordering information

| Type             | part no. |
|------------------|----------|
| DBS36E-S3AZ0S115 | 1128665  |

Other models and accessories → [www.sick.com/DBS36\\_50](http://www.sick.com/DBS36_50)

### Detailed technical data

#### Features

|                                  |   |
|----------------------------------|---|
| <b>Special device</b>            | ✓   |
| <b>Specialty</b>                 | Customized solid shaft, Diameter 5 mm, length 12.5 mm<br>Customized face mount flange (clamp collar diameter 16 mm, 3*M3 on hole circle diameter 20 mm)<br>Cable, with male connector, M12, 0.3 m, angled<br>Customer-specific pin assignment<br>IPEK part no.: 375-0222-00 |
| <b>Standard reference device</b> | DBS36E-S3AK00200, 1063728   |

#### Safety-related parameters

|  |  |
|--|--|
| <b>MTTF<sub>D</sub> (mean time to dangerous failure)</b> | 600 years (EN ISO 13849-1) <sup>1)</sup> |
|--|--|

<sup>1)</sup> This product is a standard product and does not constitute a safety component as defined in the Machinery Directive. Calculation based on nominal load of components, average ambient temperature 40°C, frequency of use 8760 h/a. All electronic failures are considered hazardous. For more information, see document no. 8015532.

#### Performance

|                                 |                                     |
|---------------------------------|-------------------------------------|
| <b>Pulses per revolution</b>    | 200                                 |
| <b>Measuring step</b>           | 90°, electric/pulses per revolution |
| <b>Measuring step deviation</b> | ± 18° / pulses per revolution       |
| <b>Error limits</b>             | ± 54° / pulses per revolution       |
| <b>Duty cycle</b>               | ≤ 0.5 ± 5 %                         |

#### Interfaces

|                                       |                        |
|---------------------------------------|------------------------|
| <b>Communication interface</b>        | Incremental            |
| <b>Communication Interface detail</b> | TTL / RS-422           |
| <b>Number of signal channels</b>      | 6-channel              |
| <b>Initialization time</b>            | < 3 ms                 |
| <b>Output frequency</b>               | ≤ 300 kHz              |
| <b>Load current</b>                   | ≤ 30 mA                |
| <b>Operating current</b>              | ≤ 50 mA (without load) |

## Electronics

|  |  |
|--|--|
| <b>Connection type</b>                         | Special version                                |
| <b>Connection type Detail</b>                  | Cable, with male connector, M12, 0.3 m, angled |
| <b>Supply voltage</b>                          | 4.5 ... 5.5 V                                  |
| <b>Reference signal, number</b>                | 1  |
| <b>Reference signal, position</b>              | 90°, electric, logically gated with A and B    |
| <b>Short-circuit protection of the outputs</b> | ✓ <sup>1)</sup>                                |

<sup>1)</sup> The short-circuit rating is only given if Us and GND are connected correctly.

## Mechanics

|                                       |  |
|---------------------------------------|--|
| <b>Mechanical design</b>              | Special version                                |
| <b>Mechanical type detail</b>         |  |
|                                       | Solid shaft, face mount flange, 5 mm x 12.5 mm |
| <b>Shaft diameter</b>                 | With flat                                      |
| <b>Weight</b>                         | + 150 g (with connecting cable)                |
| <b>Shaft material</b>                 | Stainless steel                                |
| <b>Flange material</b>                | Aluminum                                       |
| <b>Housing material</b>               | Aluminum                                       |
| <b>Material, cable</b>                | PVC  |
| <b>Start up torque</b>                | + 0.5 Ncm (+20 °C)                             |
| <b>Operating torque</b>               | 0.4 Ncm (+20 °C)                               |
| <b>Permissible movement static</b>    | <sup>1)</sup>                                  |
| <b>Permissible movement dynamic</b>   | <sup>1)</sup>                                  |
| <b>Permissible shaft loading</b>      | 40 N (radial) <sup>1)</sup><br>20 N (axial)    |
| <b>Operating speed</b>                | 6,000 min <sup>-1</sup> <sup>2)</sup>          |
| <b>Maximum operating speed</b>        | ≤ 8,000 min <sup>-1</sup> <sup>3)</sup>        |
| <b>Moment of inertia of the rotor</b> | 0.6 gcm <sup>2</sup>                           |
| <b>Bearing lifetime</b>               | 2 x 10 <sup>9</sup> revolutions                |
| <b>Angular acceleration</b>           | ≤ 500,000 rad/s <sup>2</sup>                   |

<sup>1)</sup> Higher values are possible using limited bearing life.

<sup>2)</sup> Allow for self-heating of 3.3 K per 1,000 rpm when designing the operating temperature range.

<sup>3)</sup> No permanent operation. Decreasing signal quality.

## Ambient data

|                                      |  |
|--------------------------------------|--|
| <b>EMC</b>                           | According to EN 61000-6-2 and EN 61000-6-3 (class A) |
| <b>Enclosure rating</b>              | IP65   |
| <b>Permissible relative humidity</b> | 90 % (Condensation not permitted)                    |
| <b>Operating temperature range</b>   | -20 °C ... +85 °C, -35 °C ... +95 °C on request      |
| <b>Storage temperature range</b>     | -40 °C ... +100 °C, without package                  |
| <b>Resistance to shocks</b>          | 100 g, 6 ms (EN 60068-2-27)                          |
| <b>Resistance to vibration</b>       | 20 g, 10 Hz ... 2,000 Hz (EN 60068-2-6)              |


### Certificates

|  |   |
|--|---|
| <b>EU declaration of conformity</b>  | ✓ |
| <b>UK declaration of conformity</b>  | ✓ |
| <b>ACMA declaration of conformity</b>  | ✓ |
| <b>China RoHS</b>  | ✓ |
| <b>cRUus certificate</b>   | ✓ |
| <b>Information according to Art. 3 of Data Act (Regulation EU 2023/2854)</b> | ✓ |

### Classifications

|                       |          |
|-----------------------|----------|
| <b>ECLASS 5.0</b>     | 27270501 |
| <b>ECLASS 5.1.4</b>   | 27270501 |
| <b>ECLASS 6.0</b>     | 27270590 |
| <b>ECLASS 6.2</b>     | 27270590 |
| <b>ECLASS 7.0</b>     | 27270501 |
| <b>ECLASS 8.0</b>     | 27270501 |
| <b>ECLASS 8.1</b>     | 27270501 |
| <b>ECLASS 9.0</b>     | 27270501 |
| <b>ECLASS 10.0</b>    | 27270501 |
| <b>ECLASS 11.0</b>    | 27270501 |
| <b>ECLASS 12.0</b>    | 27270501 |
| <b>ETIM 5.0</b>       | EC001486 |
| <b>ETIM 6.0</b>       | EC001486 |
| <b>ETIM 7.0</b>       | EC001486 |
| <b>ETIM 8.0</b>       | EC001486 |
| <b>UNSPSC 16.0901</b> | 41112113 |


### Dimensional drawing



Dimensions in mm (inch)


PIN assignment

View of M12 device connector on cable/housing



| Pin, 8-pin, male connector M12 | Signal TTL, HTL | Explanation                        |
|--------------------------------|-----------------|------------------------------------|
| 1                              | GND             | Ground connection of the encoder   |
| 2                              | +U <sub>S</sub> | Supply voltage                     |
| 3                              | A               | Signal line                        |
| 4                              | B               | Signal line                        |
| 5                              | Z               | Signal line                        |
| 6                              | A               | Signal line                        |
| 7                              | B               | Signal line                        |
| 8                              | Screen          | Screen                             |
| -                              | Not connected   | Not connected                      |
| -                              | Not connected   | Not connected                      |
| -                              | Not connected   | Not connected                      |
| -                              | Not connected   | Not connected                      |
| Screen                         | Screen          | Screen connecte to encoder housing |

Diagrams Signal outputs for electrical interfaces TTL and HTL



Cw with view on the encoder shaft in direction "A", compare dimensional drawing.


① Interfaces G, P, R only for channels A, B, Z.

| Supply voltage | Output                   |
|----------------|--------------------------|
| 4.5 V...5.5 V  | TTL/RS422                |
| 7 V...30 V     | TTL/RS422                |
| 7 V...30 V     | HTL/Push Pull            |
| 7 V...27 V     | HTL/push pull, 3 channel |

| Supply voltage | Output                        |
|----------------|-------------------------------|
| 4.5 V...5.5 V  | Open Collector NPN, 3 channel |
| 4.5 V...30 V   | Open Collector NPN, 3 channel |

### Recommended accessories

Other models and accessories → [www.sick.com/DBS36\\_50](http://www.sick.com/DBS36_50)

|   | Brief description   | Type       | part no. |
|---|---|------------|----------|
| shaft adaptation  |   |            |          |
|  | <ul style="list-style-type: none"> <li><b>Product segment:</b> Shaft adaptation</li> <li><b>Product:</b> Shaft couplings</li> <li><b>Description:</b> Claw coupling, shaft diameter 6 mm / 10 mm, damping element 80 shore blue, maximum shaft offset: radial ± 0.22 mm, axial ± 1 mm angular ± 1.3°, max. speed 19,000 rpm, angle of twist max. 10°, -30 °C to +80 °C, max. torque 800 Ncm, tightening torque of screws: ISO 4029 150 Ncm, material: aluminum flange, damping element: polyurethane</li> </ul> | KUP-0610-J | 2127056  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)