



# C4C-EB07530A10000

deTec

**SAFETY LIGHT CURTAINS**

**SICK**  
Sensor Intelligence.



Illustration may differ



## Ordering information

| Type              | part no. |
|-------------------|----------|
| C4C-EB07530A10000 | 1219559  |

Other models and accessories → [www.sick.com/deTec](http://www.sick.com/deTec)

## Detailed technical data

### Features

|                                |                                                                                                                                                                                                                                              |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product version</b>         | deTec4 Core IP69K                                                                                                                                                                                                                            |
| <b>Application</b>             | Areas with special hygiene requirements                                                                                                                                                                                                      |
| <b>System part</b>             | Receiver                                                                                                                                                                                                                                     |
| <b>Compatible sender</b>       | 1219558                                                                                                                                                                                                                                      |
| <b>Resolution</b>              | 30 mm                                                                                                                                                                                                                                        |
| <b>Scanning range</b>          | 12.5 m                                                                                                                                                                                                                                       |
| <b>Protective field height</b> | 750 mm                                                                                                                                                                                                                                       |
| <b>Response time</b>           | 11 ms                                                                                                                                                                                                                                        |
| <b>No blind zones</b>          | Yes                                                                                                                                                                                                                                          |
| <b>Synchronization</b>         | Optical synchronization                                                                                                                                                                                                                      |
| <b>Items supplied</b>          | Receiver in IP69K protective housing with connecting cable, 15 m<br>Test rod with diameter corresponding to the resolution of the safety light curtain<br>Safety instruction<br>Mounting instructions<br>Operating instructions for download |

### Safety-related parameters

|                                                                           |                          |
|---------------------------------------------------------------------------|--------------------------|
| <b>Type</b>                                                               | Type 4 (IEC 61496-1)     |
| <b>Safety integrity level</b>                                             | SIL 3 (IEC 61508)        |
| <b>Category</b>                                                           | Category 4 (ISO 13849-1) |
| <b>Performance level</b>                                                  | PL e (ISO 13849-1)       |
| <b>PFH<sub>D</sub> (mean probability of a dangerous failure per hour)</b> | $3.7 \times 10^{-9}$     |

|                                           |                                        |
|-------------------------------------------|----------------------------------------|
| <b>T<sub>M</sub> (mission time)</b>       | 20 years (ISO 13849-1)                 |
| <b>Safe state in the event of a fault</b> | At least one OSSD is in the OFF state. |

## Functions

|                                                            |   |
|------------------------------------------------------------|---|
| <b>Protective operation</b>                                | ✓ |
| <b>Automatic calibration of the protective field width</b> | ✓ |

## Interfaces

|                          |                                              |
|--------------------------|----------------------------------------------|
| <b>System connection</b> | Connecting cable, 15 m, flying leads, 5-wire |
| Length of cable          | 15 m                                         |
| Cable diameter           | 5 mm                                         |
| Cable material           | PUR, halogen-free                            |
| Conductor cross section  | 0.34 mm <sup>2</sup>                         |
| <b>Display elements</b>  | LEDs                                         |

## Electronics

|                                                |                                                                                      |
|------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Protection class</b>                        | III (IEC 61140)                                                                      |
| <b>Supply voltage V<sub>S</sub></b>            | 24 V DC (19.2 V ... 28.8 V)                                                          |
| <b>Ripple</b>                                  | ≤ 10 %                                                                               |
| <b>Power consumption typical</b>               | 1.92 W (DC)                                                                          |
| <b>Output signal switching devices (OSSDs)</b> |                                                                                      |
| Type of output                                 | 2 PNP semiconductors, short-circuit protected, cross-circuit monitored <sup>1)</sup> |
| ON state, switching voltage HIGH               | 24 V DC (V <sub>S</sub> – 2.25 V DC ... V <sub>S</sub> )                             |
| OFF state, switching voltage LOW               | ≤ 2 V DC                                                                             |
| Current-carrying capacity per OSSD             | ≤ 300 mA                                                                             |

<sup>1)</sup> Applies to the voltage range between –30 V and +30 V.

## Mechanics

|                                 |                                                |
|---------------------------------|------------------------------------------------|
| <b>Dimensions</b>               | See dimensional drawing                        |
| <b>Material</b>                 |                                                |
| Protective housing              | PMMA                                           |
| End caps                        | Stainless steel 1.4404                         |
| Cable glands                    | Stainless steel 1.4404 including silicone seal |
| Compensating element (membrane) | PA 6                                           |

## Ambient data

|                                      |                                                                               |
|--------------------------------------|-------------------------------------------------------------------------------|
| <b>Enclosure rating</b>              | IP65 (IEC 60529)<br>IP66 (IEC 60529)<br>IP67 (IEC 60529)<br>IP69K (ISO 20653) |
| <b>Ambient operating temperature</b> | –30 °C ... +55 °C                                                             |
| <b>Storage temperature</b>           | –30 °C ... +70 °C                                                             |
| <b>Air humidity</b>                  | 15 % ... 95 %, Non-condensing                                                 |
| <b>Vibration resistance</b>          | 5 ... 150 Hz, 3,5 mm / 1 g (EN 60068-2-6)                                     |
| <b>Shock resistance</b>              | 15 g / 6 ms (EN 60068-2-27)                                                   |
| <b>Class</b>                         | 3M4 (IEC TR 60721-4-3)                                                        |


## Certificates

|                                                                              |   |
|------------------------------------------------------------------------------|---|
| <b>EU declaration of conformity</b>                                          | ✓ |
| <b>UK declaration of conformity</b>                                          | ✓ |
| <b>ACMA declaration of conformity</b>                                        | ✓ |
| <b>Moroccan declaration of conformity</b>                                    | ✓ |
| <b>China RoHS</b>                                                            | ✓ |
| <b>ECOLAB certificate</b>                                                    | ✓ |
| <b>ULus approval</b>                                                         | ✓ |
| <b>cUL approval</b>                                                          | ✓ |
| <b>diversey certificate</b>                                                  | ✓ |
| <b>Taiwan OSHA certificate</b>                                               | ✓ |
| <b>Japan Press Safety certificate</b>                                        | ✓ |
| <b>EC-Type-Examination approval</b>                                          | ✓ |
| <b>China GB/T certificate</b>                                                | ✓ |
| <b>Information according to Art. 3 of Data Act (Regulation EU 2023/2854)</b> | ✓ |

## Classifications

|                       |          |
|-----------------------|----------|
| <b>ECLASS 5.0</b>     | 27272704 |
| <b>ECLASS 5.1.4</b>   | 27272704 |
| <b>ECLASS 6.0</b>     | 27272704 |
| <b>ECLASS 6.2</b>     | 27272704 |
| <b>ECLASS 7.0</b>     | 27272704 |
| <b>ECLASS 8.0</b>     | 27272704 |
| <b>ECLASS 8.1</b>     | 27272704 |
| <b>ECLASS 9.0</b>     | 27272704 |
| <b>ECLASS 10.0</b>    | 27272704 |
| <b>ECLASS 11.0</b>    | 27272704 |
| <b>ECLASS 12.0</b>    | 27272704 |
| <b>ETIM 5.0</b>       | EC002549 |
| <b>ETIM 6.0</b>       | EC002549 |
| <b>ETIM 7.0</b>       | EC002549 |
| <b>ETIM 8.0</b>       | EC002549 |
| <b>UNSPSC 16.0901</b> | 46171620 |

## Dimensional drawing




Dimensions in mm (inch)

- ① Operating indicator  
 ② Alignment indicator  
 ③ Optical axis

|       | S     | L1    | L2    |
|-------|-------|-------|-------|
| 300   | 311   | 469   | 454   |
| 450   | 461   | 619   | 604   |
| 600   | 611   | 769   | 754   |
| 750   | 761   | 919   | 904   |
| 900   | 911   | 1,069 | 1,054 |
| 1,050 | 1,061 | 1,219 | 1,204 |
| 1,200 | 1,211 | 1,369 | 1,354 |
| 1,350 | 1,361 | 1,519 | 1,504 |
| 1,500 | 1,511 | 1,669 | 1,654 |
| 1,650 | 1,661 | 1,819 | 1,804 |
| 1,800 | 1,811 | 1,969 | 1,954 |

## DeTec4 Core IP69K safety light curtain to RLY3-OSSD2 safety relay

**Task**

Connection of a deTec4 Core IP69K or deTec2 Core IP69K safety light curtain to RLY3-OSSD2.

Operating mode: with restart interlock and external device monitoring.

**Function**

When the protective field is clear, the OSSD1 and OSSD2 outputs carry voltage. The system can be switched on when K1 and K2 are in a fault-free de-energized position. The RLY3-OSSD2 is switched on by pressing S1 (pushbutton is pressed and released). The outputs (contacts 13-14 and 23-24) switch the K1 and K2 contactors on. When the protective field is interrupted, the OSSD1 and OSSD2 outputs switch the RLY3-OSSD2 off. Contactors K1 and K2 are switched off.

**Fault analysis**

Cross-circuits and short-circuits of the OSSDs are recognized and lead to the locking status (lock-out). A malfunction with one of the K1 or K2 contactors is detected. The switch-off function is retained. In the event of manipulation (e.g., jamming) of the S1 pushbutton, the RLY3-OSSD2 will not re-enable the output current circuits.

**Comments**

<sup>1)</sup> Output circuits: These contacts must be incorporated into the control such that the dangerous state is brought to an end if the output circuit is open. For categories 4 and 3, they must be incorporated on dual-channels (x, y paths). Type 2 devices are suitable for use up to PL c. Single-channel incorporation into the control (z path) is only possible with a singlechannel control and taking the risk analysis into account.

<sup>2)</sup> SELV/PELV safety extra-low voltage.

| Connection | Color-coded connecting cable | Sender   | Receiver |
|------------|------------------------------|----------|----------|
| 1          | Brown                        | +24 V DC | +24 V DC |
| 2          | White                        | Reserved | OSSD 1   |
| 3          | Blue                         | 0 V DC   | 0 V DC   |
| 4          | Black                        | Reserved | OSSD 2   |
| 5          | Gray                         | -        | -        |

## Recommended accessories

Other models and accessories → [www.sick.com/deTec](http://www.sick.com/deTec)

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Type          | part no. |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|----------|
| Safety relays                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |               |          |
|    | <ul style="list-style-type: none"> <li>• <b>Applications:</b> Evaluation unit</li> <li>• <b>Compatible sensor types:</b> Safety sensors with OSSDs</li> <li>• <b>Connection type:</b> Front connector with spring terminals</li> <li>• <b>Restart interlock:</b> yes</li> <li>• <b>External device monitoring (EDM):</b> Integrated</li> <li>• <b>Outputs:</b> 3 enabling current paths (safe), 2 application diagnostic outputs (not safe), 1 test pulse output (not safe)</li> <li>• <b>Housing width:</b> 18 mm</li> </ul> | RLY3-OSSD300  | 1099969  |
|    | <ul style="list-style-type: none"> <li>• <b>Applications:</b> Evaluation unit</li> <li>• <b>Compatible sensor types:</b> Safety sensors with OSSDs</li> <li>• <b>Connection type:</b> Front connector with spring terminals</li> <li>• <b>Restart interlock:</b> yes</li> <li>• <b>External device monitoring (EDM):</b> Integrated</li> <li>• <b>Outputs:</b> 2 enabling current paths (safe), 2 application diagnostic outputs (not safe), 1 test pulse output (not safe)</li> <li>• <b>Housing width:</b> 18 mm</li> </ul> | RLY3-OSSD200  | 1085344  |
| Mounting systems                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |               |          |
|   | <ul style="list-style-type: none"> <li>• <b>Description:</b> Stainless steel bracket, rotatable</li> <li>• <b>Material:</b> Stainless steel</li> <li>• <b>Details:</b> Stainless steel 1.4350, stainless steel 1.4301</li> <li>• <b>Packing unit:</b> 4 pieces</li> </ul>                                                                                                                                                                                                                                                     | BEF-2SMMEAES4 | 2023708  |
|  | <ul style="list-style-type: none"> <li>• <b>Description:</b> Stainless steel support bracket</li> <li>• <b>Material:</b> Stainless steel</li> <li>• <b>Details:</b> Stainless steel 1.4350</li> <li>• <b>Packing unit:</b> 2 pieces</li> </ul>                                                                                                                                                                                                                                                                                | BEF-2AAAADES2 | 2026849  |
|  | <ul style="list-style-type: none"> <li>• <b>Description:</b> Reinforced stainless steel bracket, rotatable</li> <li>• <b>Material:</b> Stainless steel</li> <li>• <b>Details:</b> Stainless steel 1.4350, stainless steel 1.4301</li> <li>• <b>Packing unit:</b> 4 pieces</li> </ul>                                                                                                                                                                                                                                          | BEF-2SMMVAES4 | 2026850  |
|  | <ul style="list-style-type: none"> <li>• <b>Description:</b> Reinforced stainless steel bracket, rotatable</li> <li>• <b>Material:</b> Stainless steel</li> <li>• <b>Details:</b> Stainless steel 1.4350, stainless steel 1.4301</li> <li>• <b>Packing unit:</b> 2 pieces</li> </ul>                                                                                                                                                                                                                                          | BEF-2SMMVAES2 | 2048373  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)