

S30A-6011 S3000 Standard

**SAFETY LASER SCANNERS** 

**SICK**Sensor Intelligence.



## Ordering information

Туре	part no.
S30A-6011	2022972

Other models and accessories → www.sick.com/S3000\_Standard

#### Detailed technical data

#### **Features**

Model	Sensor without system plug
Application	Indoor
Protective field range	5.5 m
Number of simultaneously monitored protective fields	≤ 4 <sup>1)</sup>
Scanning angle	190°
Angular resolution	Depending on range and resolution
Response time	60 ms <sup>2)</sup>

<sup>1)</sup> If several protective fields are monitored simultaneously, the shut-off signals must be connected to safe outputs on a Flexi Soft safety controller or routed via a safe EFI gateway.

#### Safety-related parameters

Туре	Type 3 (IEC 61496)
Safety integrity level	SIL 2 (IEC 61508)
Category	Category 3 (EN ISO 13849)
Performance level	PL d (EN ISO 13849)
$\ensuremath{PFH_D}$ (mean probability of a dangerous failure per hour)	$8.0 \times 10^{-8}$
T <sub>M</sub> (mission time)	20 years (EN ISO 13849)

#### **Functions**

External device monitoring (EDM)	✓
Integrated configuration memory	✓
Measured data output	Via RS-422
Safe SICK device communication via EFI	✓

#### **Electronics**

Protection class	II (EN 50178)

<sup>&</sup>lt;sup>2)</sup> Depending on basic response time and multiple sampling.

#### Ambient data

Enclosure rating	IP65 (EN 60529)
Ambient operating temperature	-10 °C +50 °C
Storage temperature	-25 °C +50 °C
Vibration resistance	IEC 60068-2-6, IEC 60068-2-64, IEC 60721-3-5, IEC TR 60721-4-5, IEC 61496-3
Class	5M1 (IEC 60721-3-5)
Shock resistance	IEC 60068-2-27, IEC 60721-3-5, IEC TR 60721-4-5, IEC 61496-3
Class	5M1 (IEC 60721-3-5)
Continuous shock	50 m/s², 11 ms
	100 m/s², 16 ms

# Other information

Type of light	Pulsed laser diode
Wave length	905 nm
Detectable remission factor	1.8 % > 1,000 %, reflectors
Laser class	1 (21 CFR 1040.10 and 1040.11, IEC 60825-1)

## Classifications

ECLASS 5.0	27272705
ECLASS 5.1.4	27272705
ECLASS 6.0	27272705
ECLASS 6.2	27272705
ECLASS 7.0	27272705
ECLASS 8.0	27272705
ECLASS 8.1	27272705
ECLASS 9.0	27272705
ECLASS 10.0	27272705
ECLASS 11.0	27272705
ECLASS 12.0	27272705
ETIM 5.0	EC002550
ETIM 6.0	EC002550
ETIM 7.0	EC002550
ETIM 8.0	EC002550
UNSPSC 16.0901	39121528

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

