

DOL-2321-G05MPA4

Sensor-actuator cables

CONNECTORS AND CABLES





Ordering information

Туре	part no.
DOL-2321-G05MPA4	2029220

Other models and accessories → www.sick.com/Sensor-actuator_cables



Detailed technical data

Technical specifications

Connection type head AFemale connector, M23, 21-pin, straightConnection type head BFlying leadsLocking nut materialBrass, nickel-platedCable5 m, 22-wire, PUR, halogen-freeJacket materialPUR, halogen-freeJacket colorBlackCable diameter7.8 mmConductor cross section20 x 0.15 mm² + 2 x 0.5 mm²ShieldingShieldedBending radius> 5 x cable diameterReference voltageStationary position		
Locking nut materialBrass, nickel-platedCable5 m, 22-wire, PUR, halogen-freeJacket materialPUR, halogen-freeJacket colorBlackCable diameter7.8 mmConductor cross section20 x 0.15 mm² + 2 x 0.5 mm²ShieldingShieldedBending radius> 5 x cable diameterReference voltage> 5 x cable diameter	Connection type head A	Female connector, M23, 21-pin, straight
Cable Jacket material Jacket color Black Cable diameter 7.8 mm Conductor cross section Shielding Bending radius Stationary position State to lor Black 7.8 mm 20 x 0.15 mm² + 2 x 0.5 mm² Shielded Shielded Stationary position Stationary position	Connection type head B	Flying leads
Jacket material Jacket color Black Cable diameter 7.8 mm Conductor cross section Shielding Bending radius Stationary position Reference voltage PUR, halogen-free Black 7.8 mm 20 x 0.15 mm² + 2 x 0.5 mm² Shielded > 5 x cable diameter	Locking nut material	Brass, nickel-plated
Jacket color Black Cable diameter 7.8 mm Conductor cross section 20 x 0.15 mm² + 2 x 0.5 mm² Shielding Bending radius Stationary position Reference voltage Black 7.8 mm 50 x 0.15 mm² + 2 x 0.5 mm² Shielded 50 x 0.15 mm² + 2 x 0.5 mm² Shielded 50 x 0.15 mm² + 2 x 0.5 mm² Shielded	Cable	5 m, 22-wire, PUR, halogen-free
Cable diameter 7.8 mm Conductor cross section 20 x 0.15 mm² + 2 x 0.5 mm² Shielding Shielded Bending radius Stationary position Reference voltage 7.8 mm 20 x 0.15 mm² + 2 x 0.5 mm² Shielded 5 x cable diameter	Jacket material	PUR, halogen-free
Conductor cross section Shielding Bending radius Stationary position Reference voltage 20 x 0.15 mm² + 2 x 0.5 mm² Shielded > 5 x cable diameter	Jacket color	Black
Shielding Bending radius Stationary position Reference voltage Shielded > 5 x cable diameter	Cable diameter	7.8 mm
Bending radius Stationary position > 5 x cable diameter Reference voltage	Conductor cross section	20 x 0.15 mm ² + 2 x 0.5 mm ²
Stationary position > 5 x cable diameter Reference voltage	Shielding	Shielded
Reference voltage	Bending radius	
	Stationary position	> 5 x cable diameter
	Reference voltage	
≤ 32 V		≤ 32 V
Signal type Parallel	Signal type	Parallel
Enclosure rating IP66/ IP67	Enclosure rating	IP66/ IP67
Operating temperature	Operating temperature	
Flexible use -30 °C +90 °C	Flexible use	-30 °C +90 °C
Stationary position -20 °C +130 °C	Stationary position	-20 °C +130 °C

Certificates


EU declaration of conformity	✓
China RoHS	✓

Classifications

ECLASS 5.0	19030312
ECLASS 5.1.4	19030312
ECLASS 6.0	27060304
ECLASS 6.2	27060304
ECLASS 7.0	27060304
ECLASS 8.0	27060304
ECLASS 8.1	27060304

ECLASS 9.0	27060304
ECLASS 10.0	27060304
ECLASS 11.0	27060304
ECLASS 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

Dimensional drawing



Dimensions in mm (inch)

- ① Violet
- 2 white/brown
- 3 white/green
- 4 white/yellow
- ⑤ White-gray
- 6 white/pink
- 7 White/blue
- 8 white/red
- 9 white/black
- 10 brown/green
- 1 brown/yellow
- 12 brown/gray
- ® brown/pink
- brown/blue
- (5) brown/red
- ® Green
- 1 Pink
- ® Yellow
- 19 Brown
- @ blue
- (1) Red

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

