



TPCC cooling housing DML/DMT

Cooling devices

DEVICE PROTECTION AND CARE

SICK
Sensor Intelligence.



Ordering information

Type	part no.
TPCC cooling housing DML/DMT	6036183

Other models and accessories → www.sick.com/Cooling_devices

Detailed technical data

Features

Product segment	Device protection and care
Product	Cooling devices
Description	Cooler housing, Peltier cooling unit, polyamide 6 housing
Enclosure rating	IP55 (horizontal mounting) / IP54 (vertical mounting)
Operating voltage	24 V DC ... 30 V DC
Power consumption	At 24 V DC 11 A ¹⁾
Ambient operating temperature	-40 °C ... +75 °C
Storage temperature	-40 °C ... +50 °C
Weight	+ 7.5 kg

¹⁾ Start-up current max. 15 A at 24 V DC.

Classifications

ECLASS 5.0	27279290
ECLASS 5.1.4	27279290
ECLASS 6.0	27279290
ECLASS 6.2	27279290
ECLASS 7.0	27279290
ECLASS 8.0	27279290
ECLASS 8.1	27279290
ECLASS 9.0	27279090
ECLASS 10.0	27279090
ECLASS 11.0	27279090
ECLASS 12.0	27279090
ETIM 5.0	EC002594
ETIM 6.0	EC002594
ETIM 7.0	EC002594
ETIM 8.0	EC002594
UNSPSC 16.0901	32131001

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com