



# PET-1RB250N10SVMC

PET

PRESSURE SENSORS

**SICK**  
Sensor Intelligence.



### Ordering information

| Type              | part no. |
|-------------------|----------|
| PET-1RB250N10SVMC | 6049240  |

Other models and accessories → [www.sick.com/PET](http://www.sick.com/PET)

Illustration may differ



### Detailed technical data

#### Features

|                                         |                                                               |
|-----------------------------------------|---------------------------------------------------------------|
| <b>Medium</b>                           | Fluids                                                        |
| <b>Pressure type</b>                    | Gauge pressure                                                |
| <b>Pressure unit</b>                    | bar                                                           |
| <b>Measuring range</b>                  | 0 bar ... 250 bar                                             |
| <b>Overpressure safety</b>              | 2-fold (3-fold upon request)                                  |
| <b>Process temperature</b>              | -30 °C ... +100 °C                                            |
| <b>Maximum ohmic load R<sub>A</sub></b> | > Q <sub>A</sub> , max / 1 mA [ohm] for current output signal |
| <b>Output signal</b>                    | 0 V ... 10 V, 3-wire                                          |
| <b>Initialization time</b>              | 15 ms                                                         |
| <b>Pieces per package</b>               | 50 pieces                                                     |

#### Mechanics/electronics

|                                |                                                                                                                                                  |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Communication interface</b> | -                                                                                                                                                |
| <b>Process connection</b>      | 1/4" NPT                                                                                                                                         |
| <b>Wetted parts</b>            | Process connection: 316L stainless steel<br>Measuring chamber: stainless steel 13-8 PH                                                           |
| <b>Pressure port</b>           | Standard                                                                                                                                         |
| <b>Housing material</b>        | Stainless steel 316L, PBT GF30                                                                                                                   |
| <b>Connection type</b>         | M12 round connector x 1, 4-pin                                                                                                                   |
| <b>Supply voltage</b>          | 14 V DC ... 30 V DC <sup>1)</sup>                                                                                                                |
| <b>Power consumption</b>       | 5 mA                                                                                                                                             |
| <b>Ex-approvals</b>            | 2004/108/EC, EN 61326-1 emission (group 1, class B) and interference immunity (industrial application) and pressure equipment directive 97/23/EC |
| <b>Seal</b>                    | Without seal                                                                                                                                     |
| <b>Enclosure rating</b>        | IP67 (IEC 60529) <sup>2)</sup>                                                                                                                   |

<sup>1)</sup> The pressure transmitter must be supplied with power by a limited energy circuit compliant with 9.3 of UL/EN/IEC 601010-1 or LPS to UL/EN/IEC 60950-1 or Class 2 to UL 1310/UL1585 (NEC or CEC). The power supply must be suitable for operation above 2,000 m if the pressure transmitter is used above this altitude.

<sup>2)</sup> The enclosure rating classes specified only apply while the thermometer is connected with female connectors that provide the corresponding enclosure rating.

<sup>3)</sup> Available upon request for process connections G 1/4 A according to DIN 3852-E, 1/4 " NPT, R 1/4 according to ISO 7, and 7/16"-20 UNF.

|                                    |                                                                 |
|------------------------------------|-----------------------------------------------------------------|
| <b>MTTF</b>                        | > 100 years                                                     |
| <b>Pressure peak dampening</b>     | Through integrated pressure port 0.6 mm or 0.3 mm <sup>3)</sup> |
| <b>Protection class</b>            | III                                                             |
| <b>Isolation voltage</b>           | 750 V DC                                                        |
| <b>Overvoltage protection</b>      | 36 V DC                                                         |
| <b>Short-circuit protection</b>    | Output Q <sub>A</sub> towards M                                 |
| <b>Reverse polarity protection</b> | L <sup>+</sup> towards M                                        |

<sup>1)</sup> The pressure transmitter must be supplied with power by a limited energy circuit compliant with 9.3 of UL/EN/IEC 601010-1 or LPS to UL/EN/IEC 60950-1 or Class 2 to UL 1310/UL1585 (NEC or CEC). The power supply must be suitable for operation above 2,000 m if the pressure transmitter is used above this altitude.

<sup>2)</sup> The enclosure rating classes specified only apply while the thermometer is connected with female connectors that provide the corresponding enclosure rating.

<sup>3)</sup> Available upon request for process connections G ¼ A according to DIN 3852-E, ¼ " NPT, R ¼ according to ISO 7, and 7/16"-20 UNF.

## Performance

|                                           |                                                   |
|-------------------------------------------|---------------------------------------------------|
| <b>Non-linearity</b>                      | ≤ ± 0.5 %, of span (best fit straight line, BFSL) |
| <b>Accuracy</b>                           | ≤ ± 1.2 %, of span (at room temperature)          |
| <b>Adjustment accuracy of zero signal</b> | ≤ ± 0.5 % of the span                             |
| <b>Response time</b>                      | < 2 ms                                            |
| <b>Long-term drift/one-year stability</b> | ≤ ± 0.3 % of span (per year)                      |
| <b>Rated temperature range</b>            | 0 °C ... +80 °C                                   |
| <b>Service life</b>                       | Minimum 10 Mio. load cycles                       |
| <b>Temperature error</b>                  | ≤ ± 1.5 % of the span                             |
| <b>Reference conditions</b>               | According to IEC 61298-1                          |

## Ambient data

|                                       |                                                                                       |
|---------------------------------------|---------------------------------------------------------------------------------------|
| <b>Ambient temperature, operation</b> | -30 °C ... +100 °C                                                                    |
| <b>Storage temperature</b>            | -30 °C ... +100 °C                                                                    |
| <b>Shock load</b>                     | 40 g (6 ms) according to IEC 60068-2-27 (mechanical shock)                            |
| <b>Vibration load</b>                 | 20 g (20 Hz ... 2000 Hz, 120 min) according to IEC 60068-2-6 (vibration at resonance) |

## Classifications


|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27200614 |
| <b>ECLASS 5.1.4</b> | 27200614 |
| <b>ECLASS 6.0</b>   | 27200614 |
| <b>ECLASS 6.2</b>   | 27200614 |
| <b>ECLASS 7.0</b>   | 27200614 |
| <b>ECLASS 8.0</b>   | 27200614 |
| <b>ECLASS 8.1</b>   | 27200614 |
| <b>ECLASS 9.0</b>   | 27200614 |
| <b>ECLASS 10.0</b>  | 27200614 |
| <b>ECLASS 11.0</b>  | 27200614 |
| <b>ECLASS 12.0</b>  | 27200614 |
| <b>ETIM 5.0</b>     | EC011478 |
| <b>ETIM 6.0</b>     | EC011478 |
| <b>ETIM 7.0</b>     | EC011478 |

|                |          |
|----------------|----------|
| ETIM 8.0       | EC011478 |
| UNSPSC 16.0901 | 41112410 |

Certificates


|                              |   |
|------------------------------|---|
| EU declaration of conformity | ✓ |
| UK declaration of conformity | ✓ |
| China RoHS                   | ✓ |

Dimensional drawing Process connection 1/4" NPT with round connector M12 x 1, 4-pin



Dimensions in mm (inch)

Connection type M12 round connector x 1, 4-pin



| Assignment | L <sup>+</sup> | M | Q <sub>A</sub> |
|------------|----------------|---|----------------|
| 2-wire     | 1              | 3 | -              |
| 3-wire     | 1              | 3 | 4              |

- ① L<sup>+</sup>: Positive supply connection  
② M: Negative supply connection  
③ Q<sub>A</sub>: Analog output

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)