


SICK.COM



DATA SHEET

# LBR-XXCSDAMHAAX

LBR SicWave  
Level sensors

**SICK** Sensor Intelligence

## LEVEL SENSORS

## LBR-XXCSDAMHAAX

## ORDERING INFORMATION

Type	part no.
LBR-XXCSDAMHAAX	6083868

Further device versions and accessories at [www.sick.com/LBR\\_SicWave](http://www.sick.com/LBR_SicWave)



## DETAILED TECHNICAL DATA

## FEATURES

Medium	Bulk solids
Measurement	Continuous
Probe type	Metal jacketed lens antenna / PEEK / c/w air purge connection
Frequency band	W-band (within 75 ... 85 GHz)
Measuring range	Up to 120 m (393.7 ft), recommended measuring range in thread version with integrated horn antenna up to 20 m (65.62 ft)
Angle of dispersion	4° <sup>1)</sup>
Process pressure	-1 bar ... 3 bar (-100 kPa ... 300 kPa / -14.5 psig ... 43.5 psig)
Process temperature	-40 °C ... +130 °C
RoHS certificate	✓
HART	✓
Display	Installed
Control element	Pushbutton operation

<sup>1)</sup> Outside the specified aperture angle, the level of the radar signal energy is lowered by 50% (-3 dB).

## PERFORMANCE

Accuracy of sensor element	≤ 5 mm <sup>1)</sup>
Non-repeatability	≤ 1 mm

<sup>1)</sup> Measurement distance > 0.25 m / 0.8202 ft.

<sup>2)</sup> Time span after abrupt change to the measurement distance by max. 2 m for bulk material applications until the output signal has assumed 90% of its steady-state value for the first time (IEC 61298-2).

Digital measurement resolution	< 1 mm
Analog measurement resolution	0.3 $\mu$ A
Digital output temperature drift	$\leq$ 3 mm / 10 K, max. 10 mm
Current output temperature drift	$\leq$ 0.03% / 10 K relating to the 16 mA span or $\leq$ 0.3%
Deviation on current output due to digital-analog conversion	< 15 $\mu$ A
Measurement cycle time	Approx. 700 ms
Step response time	$\leq$ 3 s <sup>2)</sup>
MTBF	3,37*10 <sup>6</sup> h
Display	✓

<sup>1)</sup> Measurement distance > 0.25 m / 0.8202 ft.

<sup>2)</sup> Time span after abrupt change to the measurement distance by max. 2 m for bulk material applications until the output signal has assumed 90% of its steady-state value for the first time (IEC 61298-2).

## ELECTRONICS

Communication interface	HART
Supply voltage	9 V DC ... 30 V DC <sup>1)</sup>
Protection class	I (IEC 61010-1)
Connection type	M20 x 1.5 / cable gland PA black ( $\varnothing$ 5 mm - 9 mm)
Output signal	4 mA ... 20 mA / HART <sup>2)</sup>
Contamination rating	4
Enclosure rating	IP66 / IP68
EMC	EN 61326-1
Start-up current	< 3.6 mA
Overvoltage category	III (IEC 61010-1)
Short-circuit protection	✓
Isolation	✓

<sup>1)</sup> All connections are polarity protected. All outputs are overload and short-circuit protected.

<sup>2)</sup> Range of the output signal: 3.8 mA ... 20.5 mA / HART (factory setting); fault current < 3.6 mA or 22 mA.

## MECHANICS

Process connection	Swivel holder with flange 4" 150 lb / 316/316L
Housing material	Aluminum
Housing design	Single-chamber housing
Sealing material	FKM (SHS FPM 70C3 GLT)
Antenna material	PEEK

## AMBIENT DATA

Ambient operating temperature	-40 °C ... +80 °C
Ambient temperature, storage	-40 °C ... +80 °C

Further information as well as suitable accessories, example applications and downloads such as CAD dimensional models, operating instructions and software can be found at [www.sick.com/6083868](http://www.sick.com/6083868)



SICK AG  
WALDKIRCH  
GERMANY  
SICK.COM

# SICK AT A GLANCE

SICK is a leading global technology company for intelligent sensors and integrated solutions in industrial automation. Our technologies set benchmarks, making your industrial processes more efficient, safer and more sustainable – both in logistics and manufacturing operations.

SICK combines sensor intelligence with industry expertise and certified consulting services. We provide the ideal foundation for scalable as well as tailor-made automation solutions and create added value along the entire value chain. Our close partnerships with our customers are more than just a promise: Together, we optimize productivity, improve quality, protect health and safety, and help build a sustainable future. All with empathy and trust.

Since 1946, we have been developing innovative technologies with passion and a pioneering spirit. With a global network in around 40 countries, SICK has a global presence and is always close by. The company's headquarters are located in Waldkirch near Freiburg, Germany. Our customers benefit from our understanding of both local and global requirements, which enables us to deliver tailor-made solutions

**SICK**  
Sensor Intelligence