



# KTX-WB41142242ZZZ

## KTX

CONTRAST SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



## Ordering information

| Type              | part no. |
|-------------------|----------|
| KTX-WB41142242ZZZ | 1137287  |

Other models and accessories → [www.sick.com/KTX](http://www.sick.com/KTX)

## Detailed technical data

## Features

|                                   |                         |
|-----------------------------------|-------------------------|
| <b>Parameter presets</b>          | None                    |
| <b>Special applications</b>       | Standard                |
| <b>Device type</b>                | Easy Teach              |
| <b>Housing design</b>             | Large                   |
| <b>Dimensions (W x H x D)</b>     | 30 mm x 53 mm x 78.5 mm |
| <b>Light source</b>               | LED, RGB <sup>1)</sup>  |
| <b>Light emission</b>             | Short device side       |
| <b>Light spot size</b>            | 0.9 mm x 3.8 mm         |
| <b>Light spot direction</b>       | Vertical <sup>2)</sup>  |
| <b>Receiving filters</b>          | None                    |
| <b>Wave length</b>                | 470 nm, 525 nm, 625 nm  |
| <b>Sensing distance</b>           | ≤ 13 mm                 |
| <b>Sensing distance tolerance</b> | ± 3 mm                  |
| <b>Teach-in mode</b>              | 2-point teach-in        |
| <b>Output function</b>            | Light/dark switching    |
| <b>Delay time</b>                 | Adjustable              |
| <b>Setting the key lock</b>       | Standard                |
| <b>Delivery status</b>            | 2-point teach-in        |
| <b>Safety-related parameters</b>  |                         |
| MTTF <sub>D</sub>                 | 291 years               |

<sup>1)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.<sup>2)</sup> In relation to long side of housing.

## Electronics

|  |   |
|--|---|
| <b>Supply voltage</b>                              | 10.8 V DC ... 28.8 V DC <sup>1)</sup>   |
| <b>Ripple</b>                                      | $\leq 5 \text{ V}_{\text{pp}}$ <sup>2)</sup>  |
| <b>Current consumption</b>                         | < 100 mA <sup>3)</sup>  |
| <b>Switching frequency</b>                         | 25 kHz <sup>4)</sup>  |
| <b>Response time</b>                               |   |
|  | 20 $\mu\text{s}$  |
| <b>Jitter</b>                                      | 10 $\mu\text{s}$  |
| <b>Switching output</b>                            | Push-pull: PNP/NPN  |
| <b>Switching output (voltage)</b>                  | Push-pull: PNP/NPN HIGH = $U_V - 3 \text{ V}$ / LOW $\leq 3 \text{ V}$  |
| <b>Output current <math>I_{\text{max.}}</math></b> | 100 mA <sup>5)</sup>  |
| <b>Retention time (ET)</b>                         | 35 ms, non-volatile memory  |
| <b>Time delay</b>                                  | None  |
| <b>Protection class</b>                            | III   |
| <b>Circuit protection</b>                          | $U_V$ connections, reverse polarity protected<br>Output Q short-circuit protected<br>Interference pulse suppression |
| <b>Connection type</b>                             | Male connector M12, 4-pin   |

<sup>1)</sup> Limit values: DC 12 V (-10 %) ... DC 24 V (+20 %). Operation in short-circuit protected network max. 8 A.

<sup>2)</sup> May not fall below or exceed  $U_V$  tolerances.

<sup>3)</sup> Without load.

<sup>4)</sup> With light/dark ratio 1:1.

<sup>5)</sup> Total current of all Outputs.

## Mechanics

|                         |         |
|-------------------------|---------|
| <b>Housing material</b> | VISTAL® |
| <b>Optics material</b>  | COP     |
| <b>Weight</b>           | 94 g    |

## Ambient data

|                                      |  |
|--------------------------------------|--|
| <b>Ambient operating temperature</b> | -20 °C ... +60 °C                        |
| <b>Ambient temperature, storage</b>  | -25 °C ... +75 °C                        |
| <b>Shock load</b>                    | According to IEC 60068-2-27 (30 g/11 ms) |
| <b>Enclosure rating</b>              | IP67                                     |
| <b>UL File No.</b>                   | E181493                                  |

## Classifications


|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27270906 |
| <b>ECLASS 5.1.4</b> | 27270906 |
| <b>ECLASS 6.0</b>   | 27270906 |
| <b>ECLASS 6.2</b>   | 27270906 |
| <b>ECLASS 7.0</b>   | 27270906 |
| <b>ECLASS 8.0</b>   | 27270906 |
| <b>ECLASS 8.1</b>   | 27270906 |

|                       |          |
|-----------------------|----------|
| <b>ECLASS 9.0</b>     | 27270906 |
| <b>ECLASS 10.0</b>    | 27270906 |
| <b>ECLASS 11.0</b>    | 27270906 |
| <b>ECLASS 12.0</b>    | 27270906 |
| <b>ETIM 5.0</b>       | EC001820 |
| <b>ETIM 6.0</b>       | EC001820 |
| <b>ETIM 7.0</b>       | EC001820 |
| <b>ETIM 8.0</b>       | EC001820 |
| <b>UNSPSC 16.0901</b> | 39121528 |

## Certificates

|  |   |
|--|---|
| <b>EU declaration of conformity</b>          | ✓ |
| <b>UK declaration of conformity</b>          | ✓ |
| <b>ACMA declaration of conformity</b>        | ✓ |
| <b>Moroccan declaration of conformity</b>    | ✓ |
| <b>China RoHS</b>                            | ✓ |
| <b>cULus certificate</b>                     | ✓ |
| <b>Photobiological safety (IEC EN 62471)</b> | ✓ |


## Dimensional drawing



Dimensions in mm (inch)


- ① Optical axis
- ② Threaded mounting hole M5
- ③ M12 male connector, delivery state
- ④ M12 male connector, end stop right
- ⑤ M12 male connector, end stop left
- ⑥ display and adjustment elements

## display and adjustment elements




- ① Bar graph
- ② single teach-in button
- ③ LED status indicator

## Connection diagram Cd-380




## KTS Core - setting the switching threshold (2-point teach-in)

Suitable for manual positioning of the object to be detected, e.g. marks and background.

**1. Position mark**

When setting the contrasts to be detected, the first LED (green) flashes in the bar graph. Press set button.


**2. Position background**

When setting the contrasts to be detected, the second LED (green) flashes in the bar graph. Press set button. The Quality of Teach is displayed.

## KTS Core Easy Teach - Setting the switching threshold


Suitable for manual positioning of the object to be detected, e.g. marks and background.

### 1. Position mark




When setting the contrasts to be detected, the first LED (green) flashes in the bar graph.  
Press Teach-in pushbutton.

### 2. Position background



When setting the contrasts to be detected, the second LED (green) flashes in the bar graph.  
Press Teach-in pushbutton.

### Example



### Switching characteristics


The optimum emitted light is selected automatically (at RGB variants).  
Static teach-in: light/dark setting is defined using teach-in sequence.

Keylock (activation and deactivation): Press and hold the Teach-in pushbutton > 10 s.

Teach-in failure: The Q-LED (yellow) flashes and all LEDs flash on the bar graph (green).

## Sensing distance

Sensitivity in %



## Recommended accessories

Other models and accessories → [www.sick.com/KTX](http://www.sick.com/KTX)

|   | Brief description   | Type               | part no. |
|---|---|--------------------|----------|
| Mounting systems  |   |                    |          |
|  | <ul style="list-style-type: none"> <li><b>Description:</b> Plate G for universal clamp bracket</li> <li><b>Material:</b> Steel</li> <li><b>Details:</b> Steel, zinc coated</li> <li><b>Items supplied:</b> Universal clamp (2022726), mounting hardware</li> <li><b>Usable for:</b> W34, LUT3, KT5-2, KT10, CS8, W24-2, KT8, KT8</li> </ul>   | BEF-KHS-G01        | 2022464  |
| connectors and cables   |   |                    |          |
|  | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Male connector, M12, 4-pin, straight, A-coded</li> <li><b>Description:</b> Unshielded</li> <li><b>Connection systems:</b> Screw-type terminals</li> <li><b>Permitted cross-section:</b> <math>\leq 0.75 \text{ mm}^2</math></li> </ul>  | STE-1204-G         | 6009932  |
|  | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M12, 4-pin, straight, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 5 m, 4-wire, PVC</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> <li><b>Application:</b> Zones with chemicals, Uncontaminated zones</li> </ul> | YF2A14-050VB3XLEAX | 2096235  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is "Sensor Intelligence."**

## WORLDWIDE PRESENCE:

Contacts and other locations [www.sick.com](http://www.sick.com)