SICK.COM




DATA SHEET

# M40S-67A105AA0, M40E-67A105RA0

M4000 Area
Safety light curtains

SICK Sensor Intelligence




Illustration may differ

## SAFETY LIGHT CURTAINS

# M40S-67A105AA0, M40E-67A105RA0

### ORDERING INFORMATION

| System part | Type | part no. |
|---|---|---|
| sender | M40S-67A105AA0 | 1200604 |
| receiver | M40E-67A105RA0 | 1200605 |

Further device versions and accessories at www.sick.com/M4000_Area

## DETAILED TECHNICAL DATA

### FEATURES

| | |
|---|---|
| System part | Pair |
| Resolution | 80 mm |
| Scanning range | 90 m |
| Protective field height | 1,350 mm |
| Synchronization | Optical synchronization |

### SAFETY-RELATED PARAMETERS

| | |
|---|---|
| Type | Type 4 (IEC 61496-1) |
| Safety integrity level | SIL 3 (IEC 61508) |
| Category | Category 4 (EN ISO 13849) |
| Performance level | PL e (EN ISO 13849) |
| $T_M$ (mission time) | 20 years (EN ISO 13849) |
| Safe state in the event of a fault | At least one OSSD is in the OFF state. |

### FUNCTIONS

| | Functions | Delivery status |
|---|---|---|
| Restart interlock | ✓ | Internal |
| External device monitoring (EDM) | ✓ | Activated |
| Beam coding | ✓ | Uncoded |
| Configurable status output (ADO) | ✓ | Contamination (OWS) |
| Sender test | ✓ | Deactivated |
| Configurable scanning range | ✓ | Low scanning range |
| Safe SICK device communication via EFI | ✓ | |

## INTERFACES

| | |
|---|---|
| System connection | |
| Connection type | Hirschmann male connector M26, 12-pin |
| Configuration method | PC with CDS (Configuration and Diagnostic Software) |
| Configuration connection | Female connector M8, 4-pin |
| Display elements | 7-segment display, LEDs |
| Status display | LEDs |

## ELECTRONICS

| | |
|---|---|
| Protection class | III (IEC 61140) |
| Supply voltage $V_S$ | 24 V DC (19.2 V DC ... 28.8 V DC) |
| Residual ripple | ≤ 10 % [1] |
| Power consumption | ≤ 0.6 A [2]<br>≤ 0.2 A |
| Output signal switching devices (OSSDs) | |
| Type of output | 2 PNP semiconductors, short-circuit protected, cross-circuit monitored [3] |

[1] Within the limits of $V_S$.

[2] Without load.

[3] Applies to the voltage range between –30 V and +30 V.

## MECHANICS

| | |
|---|---|
| Housing cross-section | 52 mm x 55.5 mm |
| Housing material | Aluminum alloy ALMGSI 0.5 |
| Surface treatment | Powder coated |
| Front screen material | Polycarbonate, scratch-resistant coating |


## AMBIENT DATA

| | |
|---|---|
| Enclosure rating | IP65 (EN 60529) |
| Ambient operating temperature | –30 °C ... +55 °C |
| Storage temperature | –30 °C ... +70 °C |
| Air humidity | 15 % ... 95 %, Non-condensing |
| Vibration resistance | 5 g, 10 Hz ... 55 Hz (EN 60068-2-6) |
| Shock resistance | 10 g, 16 ms (EN 60068-2-27) |

## OTHER INFORMATION

| | |
|---|---|
| Wave length | 850 nm |

**DIMENSIONAL DRAWING**




Dimensions in mm (inch)

| Length of the monitored area S | L1 | L2 |
|---|---|---|
| 300 (11.81) | 387 (15.24) | 416 (16.38) |
| 450 (17.72) | 537 (21.14) | 566 (22.28) |
| 600 (23.62) | 687 (27.05) | 716 (28.19) |
| 750 (29.53) | 837 (32.95) | 866 (34.09) |
| 900 (35.43) | 987 (38.86) | 1,016 (40.00) |
| 1,050 (41.34) | 1,137 (44.76) | 1,166 (45.91) |
| 1,200 (47.24) | 1,287 (50.67) | 1,316 (51.81) |
| 1,350 (53.15) | 1,437 (56.57) | 1,466 (57.72) |
| 1,500 (59.06) | 1,587 (62.48) | 1,616 (63.62) |
| 1,650 (64.96) | 1,737 (68.39) | 1,766 (69.53) |

| Length of the monitored area S | L1 | L2 |
|---|---|---|
| 1,800 (70.87) | 1,887 (74.29) | 1,916 (75.43) |

Further information as well as suitable accessories, example applications and downloads such as CAD dimensional models, operating instructions and software can be found at www.sick.com/1200604

SICK AG
WALDKIRCH
GERMANY
SICK.COM

# SICK AT A GLANCE

SICK is a leading global technology company for intelligent sensors and integrated solutions in industrial automation. Our technologies set benchmarks, making your industrial processes more efficient, safer and more sustainable – both in logistics and manufacturing operations.

SICK combines sensor intelligence with industry expertise and certified consulting services. We provide the ideal foundation for scalable as well as tailor-made automation solutions and create added value along the entire value chain. Our close partnerships with our customers are more than just a promise: Together, we optimize productivity, improve quality, protect health and safety, and help build a sustainable future. All with empathy and trust.

Since 1946, we have been developing innovative technologies with passion and a pioneering spirit. With a global network in around 40 countries, SICK has a global presence and is always close by. The company's headquarters are located in Waldkirch near Freiburg, Germany. Our customers benefit from our understanding of both local and global requirements, which enables us to deliver tailor-made solutions

SICK

Sensor Intelligence