




W26

Stars in object detection

SICK
Sensor Intelligence.

Advantages



Easy and quick sensor alignment using BluePilot

Using the innovative BluePilot alignment aid, the sensors in the W16 and W26 product family can be commissioned in seconds. The blue LED display provides direct feedback to assist you with optimally aligning the sensors and reflectors as well as senders and receivers. In the case of the photoelectric proximity sensors, a push-and-turn mechanism enables the sensor to be adjusted quickly and precisely, thereby eliminating the customary time-consuming fine adjustment using rotary controls.

BluePilot also reports any change in detection quality, e.g., due to contamination or vibrations, which ensures faults are detected in a timely manner, long before a production downtime occurs.

Faster, convenient start-up



Photoelectric retro-reflective and through-beam photoelectric sensors

- The blue LED alignment aid speeds up the process of optimally aligning the sensors and reflectors or senders and receivers
- Any changes in the operational safety due to contamination or vibrations can be recognized at a glance



Photoelectric proximity switch

- Select the right mode for the object type in question by simply rotating the control element



Photoelectric retro-reflective sensor for detecting transparent objects

- Select the right mode for the object type in question by simply rotating the control element



With the new BluePilot operating concept, you will save valuable time commissioning the sensor, and avoid production downtimes thanks to the timely reporting of faults.




Rugged and reliable

The sensors from the W26 product family are particularly rugged and reliable.


With the OptoFilter, the sensors see what they have to see: they are immune to LED lights, reflections from safety vests and the influence of depolarizing objects.

The sensors can also withstand many chemical, thermal and mechanical environmental influences thanks to the ultra-rugged VISTAL housing.

Everything reliably detected




For uneven, shiny, reflective and even jet black objects, Twin-Eye technology offers a high level of operational safety. Two receivers in one sensor ensure a high detection reliability. Find out more in the video



Thanks to foreground suppression, the sensors reliably detect very flat, poorly remitting, reflective, and uneven objects. Find out more in the video



Thanks to the OptoFilter, the sensors feature high ambient light immunity. Find out more in the video



Thanks to the VISTAL housing, the sensors can also withstand extreme loads. Find out more in the video



The devices comply with category 3D / 3G and can be used in "Zone 22: Non-conductive dusts" and "Zone 2" explosion-hazardous areas.



The rugged design ensures high system availability and reduces down-times.




Smart sensors for efficient machine communication


Smart Sensors provide indispensable input for every process chain. They support dynamic, real-time-optimized, and self-organized industry processes. The Smart Sensors W16 and W26 capture real-life situations, and generate and receive data and information beyond traditional switching signals or measured process parameters.

[Find out more](https://www.sick.de/smart-sensors)


From raw signals to customized information



Base logic: User-definable logic functions with trigger sensors and switching signal delays



Time measurement and debouncing with the aid of the Time Measurement and Debouncing Smart Task



W26 with the Counter and Debouncing Smart Task counts and evaluates detection signals



Interconnectivity and efficient processing of data ensure leaner structures and cost benefits for your process.




Technical data overview

Dimensions (W x H x D)	24.6 mm x 82.5 mm x 53.3 mm 20 mm x 55.7 mm x 42 mm 31.4 mm x 112.3 mm x 70.4 mm
Sensing range max.	
Light source	PinPoint LED / LED (depends on variant)
Type of light	Visible red light / Infrared light (depends on variant)
Enclosure rating	IP66 IP67 IP69 IP65 (depends on variant)
Housing material	Plastic

Product description

To ensure a reliable object detection, the W26 photoelectric sensors from SICK are equipped with TwinEye or Spot Size Recognition technology, depending on the variant. Thanks to the BluePilot operating and display concept, the sensors are adjusted quickly and easily. They can be configured for the specific application via IO-Link and offer additional diagnostic functions. Well-visible red PinPoint LEDs and infrared LEDs serve as the light source. The W26 sensors deliver reliable detection thereby reducing unplanned machine downtimes. Ready-to-install variants with metal housings are available for explosion-hazardous areas that meet the requirements of device categories 3D and 3G according to ATEX.



At a glance

- BluePilot: Optical alignment aid, adjustment of the sensing range via Teach-Turn adjustment with optical sensing range indicator or via IO-Link
- PinPoint LED: Light-intensive red sender LED
- Technologies: TwinEye, Spot Size Recognition (SSR)
- Enhanced Sensing, IO-Link, diagnostics
- Sensors correspond to the 3D / 3G category

Your benefits

- User-friendly thanks to optical sensing range indicator on the housing or via IO-Link
- Easy alignment of the light beam to the reflector, receiver or object thanks to the well-visible light spot of the PinPoint LED and the blue LED display
- Very reliable thanks to innovative detection technologies and rugged optics
- Increases the speed, efficiency and transparency of machine processes through Smart Sensor functions, makes predictive maintenance possible
- Ready-to-install sensors with metal housing in accordance with category 3D / 3G for explosion-hazardous areas
-

Fields of application

- Consumer goods
- Automotive and parts suppliers
- Wood
- Storage and conveyor
- Handling and assembly
- Metal and steel
- Stone, ceramic, glass
- Textile

Ordering information

Other models and accessories → www.sick.com/W26

- **Sensing range min. / max.:** 0 m / 60 m
- **Functional principle:** Through-beam photoelectric sensor
- **Switching output:** push-pull: PNP/NPN
- **Housing:** rectangular

Switching mode	Light source	Type of light	Connection type	Type	Part no.
Light switching	PinPoint LED	Visible red light	Male connector M12, 4-pin	WSE26P-24165100A00	1118267
Light/dark switching	LED	Infrared light	Cable with M12 male connector, 4-pin, 318 mm	WSE26I-34162100A00	1088333
			Cable, 4-wire, 2 m	WSE26I-1H162100A00	1088334
			Male connector M12, 4-pin	WSE26I-24162100A00	1088332
	PinPoint LED	Visible red light	Cable with M12 male connector, 4-pin, 318 mm	WSE26P-34162100A00	1088336
			Cable with Q6 male connector, 6-pin, DC-coded, 298 mm	WSE26P-39112102ZZZ	1102912
			Cable with Q7 male connector, 7-pin, DC-coded, 298 mm	WSE26P-3B112100ZZZ	1102913
			Cable, 4-wire, 10 m	WSE26P-X01	1131860
			Cable, 4-wire, 2 m	WSE26P-1H162100A00	1088337
			Male connector M12, 4-pin	WSE26P-24162100A00	1088335
				1102909	

- **Sensing range min. / max.:** 5 m / 120 m
- **Functional principle:** Through-beam photoelectric sensor
- **Switching mode:** Light/dark switching
- **Switching output:** push-pull: PNP/NPN

Light source	Type of light	Connection type	Housing	Type	Part no.
LED	Visible red light	Male connector M12, 4-pin	Rectangular	WSE26G-24162400A00	1127145

- **Sensing range min. / max.:** 0.25 m / 19 m
- **Functional principle:** Photoelectric retro-reflective sensor
- **Functional principle detail:** With minimum distance to reflector (dual lens system)
- **Switching mode:** Light/dark switching
- **Switching output:** push-pull: PNP/NPN
- **Light source:** PinPoint LED
- **Type of light:** visible red light
- **Housing:** rectangular

Connection type	Type	Part no.
Cable with M12 male connector, 4-pin, 318 mm	WLD26P-341121A0ZZZ	1221733
Cable, 4-wire, 2 m	WLD26P-1H1121A0ZZZ	1218805
Male connector M12, 4-pin	WLD26P-241121A0ZZZ	1218699

- **Sensing range min. / max.:** 0.25 m / 3 m
- **Functional principle:** Photoelectric retro-reflective sensor
- **Functional principle detail:** With minimum distance to reflector (dual lens system)
- **Switching mode:** Light/dark switching
- **Switching output:** push-pull: PNP/NPN

Light source	Type of light	Connection type	Housing	Type	Part no.
PinPoint LED	Visible red light	Male connector M12, 4-pin	Rectangular	WLD26P-241122A0ZZZ	1113466

- **Sensing range min. / max.:** 10 mm / 1,000 mm
- **Functional principle:** Photoelectric proximity sensor
- **Functional principle detail:** Background suppression, TwinEye technology
- **Switching output:** push-pull: PNP/NPN
- **Housing:** rectangular

Switching mode	Light source	Type of light	Connection type	Type	Part no.	
–	PinPoint LED	Visible red light	Male connector M12, 4-pin	WTS26P-24161120A70	1219799	
				WTS26P-2416H120A71	1219800	
Light/dark switching	LED	Infrared light	Male connector M12, 4-pin	WTS26I-24161120A00	1137249	
				PinPoint LED	Visible red light	Cable with M12 male connector, 4-pin, 318 mm
	Cable, 4-wire, 2 m	WTS26P-1H161120A00	1218950			
		Male connector M12, 4-pin	WTS26P-24161120A00			
	WTS26P-24162120A00		1221727			

- **Sensing range min. / max.:** 10 mm / 500 mm
- **Functional principle:** Photoelectric proximity sensor
- **Functional principle detail:** Background suppression, TwinEye technology
- **Switching mode:** Light/dark switching
- **Switching output:** push-pull: PNP/NPN

Light source	Type of light	Connection type	Housing	Type	Part no.
LED	Visible red light	Male connector M12, 4-pin	Rectangular	WTS26G-24161920A00	1128822

- **Sensing range min. / max.:** 0 m / 18 m
- **Functional principle:** Photoelectric retro-reflective sensor
- **Functional principle detail:** Without reflector minimum distance (autocollimation/coaxial optics)
- **Light source:** PinPoint LED
- **Type of light:** visible red light
- **Housing:** rectangular

Switching mode	Switching output	Connection type	Type	Part no.
Dark switching	Push-pull: PNP/NPN	Male connector M12, 4-pin	WLA26P-24114100ZZZ	1222793
			WLA26P-2416A100A00	1222697

Switching mode	Switching output	Connection type	Type	Part no.
Light switching	Push-pull: PNP/NPN	Male connector M12, 4-pin	WLA26P-24116100ZZZ	1222792
			WLA26P-24165100A00	1147172
Light/dark switching	PNP	Male connector M12, 4-pin	WLA26P-24862130A00	1115760
			Push-pull: PNP/NPN	Cable with M12 male connector, 4-pin, 318 mm
	WLA26P-X01	1131858		
	Cable with Q6 male connector, 6-pin, DC-coded, 298 mm	WLA26P-39421102ZZZ	1222790	
		WLA26P-39722102ZZZ	1222819	
	Cable with Q7 male connector, 7-pin, DC-coded, 298 mm	WLA26P-3B112100ZZZ	1222791	
	Cable, 4-wire, 10 m	WLA26P-X02	1131859	
	Cable, 4-wire, 2 m	WLA26P-1H162100A00	1218822	
	Male connector M12, 4-pin	WLA26P-24161100A00	1221732	
		WLA26P-24162100A00	1218664	
		WLA26P-24162130A00	1111236	
1111293				

- **Sensing range min. / max.:** 30 mm / 1,600 mm
- **Functional principle:** Photoelectric proximity sensor
- **Functional principle detail:** Background suppression
- **Switching mode:** Light/dark switching
- **Light source:** PinPoint LED
- **Type of light:** visible red light
- **Housing:** rectangular

Switching output	Connection type	Type	Part no.
PNP	Male connector M12, 4-pin	WTB26P-24861120A00	1115766
Push-pull: PNP/NPN	Cable with M12 male connector, 4-pin, 318 mm	WTB26P-34161120A00	1218806
		WTB26P-X01	1131855
	Cable with Q6 male connector, 6-pin, DC-coded, 298 mm	WTB26P-39422122ZZZ	1222809
		WTB26P-39721122ZZZ	1222804
	Cable with Q7 male connector, 7-pin, DC-coded, 298 mm	WTB26P-3B111120ZZZ	1222816
	Cable, 4-wire, 2 m	WTB26P-1H161120A00	1218824
		WTB26P-1H162120A00	1222744
	Male connector M12, 4-pin	WTB26P-24161120A00	1218666

- **Sensing range min. / max.:** 30 mm / 1,600 mm
- **Functional principle:** Photoelectric proximity sensor
- **Functional principle detail:** Background suppression, NarrowBeam
- **Switching output:** push-pull: PNP/NPN
- **Light source:** PinPoint LED
- **Type of light:** visible red light
- **Connection type:** male connector M12, 4-pin
- **Housing:** rectangular

Switching mode	Type	Part no.
Light switching	WTB26P-24113520ZZZ	1222813
Light/dark switching	WTB26P-24161520A00	1222705

- **Sensing range min. / max.:** 30 mm / 3,000 mm
- **Functional principle:** Photoelectric proximity sensor
- **Functional principle detail:** Background suppression
- **Housing:** rectangular

Switching mode	Switching output	Light source	Type of light	Connection type	Type	Part no.
Dark switching	Push-pull: PNP/NPN	PinPoint LED	Visible red light	Male connector M12, 4-pin	WTB26P-24115420ZZZ	1147510
Light switching	Push-pull: PNP/NPN	PinPoint LED	Visible red light	Male connector M12, 4-pin	WTB26P-24113420ZZZ	1140316
Light/dark switching	NPN	LED	Infrared light	Male connector M12, 4-pin	WTB26I-24G11420ZZZ	1124859
					1133143	
	PNP	LED	Infrared light	Male connector M12, 4-pin	WTB26I-24861420A00	1123835
					WTB26I-24861421A00	1126768
					WTB26I-1H161420A00	1222713
	Push-pull: PNP/NPN	LED	Infrared light	Cable, 4-wire, 2 m	WTB26I-1H162420A00	1222712
					WTB26I-24161420A00	1222711
					WTB26I-24161422A00	1109760
					WTB26I-24162420A00	1222675
PinPoint LED	Visible red light	Cable with M12 male connector, 4-pin, 318 mm	Male connector M12, 4-pin	WTB26P-34161420A00	1125296	
				WTB26P-24161420A00	1222709	

- **Sensing range min. / max.:** 30 mm / 2,000 mm
- **Functional principle:** Photoelectric proximity sensor
- **Functional principle detail:** Background suppression
- **Switching output:** push-pull: PNP/NPN
- **Light source:** LED
- **Type of light:** Infrared light
- **Housing:** rectangular

Switching mode	Connection type	Type	Part no.
Dark switching	Male connector M12, 4-pin	WTB26I-24115120ZZZ	1222815
		WTB26I-24116120ZZZ	1222814

Switching mode	Connection type	Type	Part no.
Light/dark switching	Cable with M12 male connector, 4-pin, 318 mm	WTB26I-34161120A00	1218827
		WTB26I-X03	1131857
	Cable with Q6 male connector, 6-pin, DC-coded, 298 mm	WTB26I-39422122ZZZ	1222810
		WTB26I-39721122ZZZ	1222808
	Cable with Q7 male connector, 7-pin, DC-coded, 298 mm	WTB26I-3B111120ZZZ	1222817
	Cable, 4-wire, 10 m	WTB26I-X02	1131856
	Cable, 4-wire, 2 m	WTB26I-1H161120A00	1218825
	Male connector M12, 4-pin	WTB26I-24161120A00	1218667
		WTB26I-24161122A00	1222797
		WTB26I-24162120A00	1221726
		WTB26I-24162122A00	1222796

- **Sensing range min. / max.:** 0 mm / 800 mm
- **Functional principle:** Photoelectric proximity sensor
- **Functional principle detail:** Foreground suppression
- **Switching mode:** Light/dark switching
- **Switching output:** push-pull: PNP/NPN

Light source	Type of light	Connection type	Housing	Type	Part no.
PinPoint LED	Visible red light	Male connector M12, 4-pin	Rectangular	WTF26P-24161420A00	1113470

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com